

Dynacom DN6108P SERIES 8CH 960P/8CH 1080P POE NVR



- P2P cloud service, including cloud connecting, cloud monitoring, cloud transmitting to access IPC and NVR at any time and any place
- Support Onvif protocol, support High profile S, High profile G, compatible with different IP camera that based on Onvif, RTSP standard
- Support megapixel HD network video preview, storage and playback;
- Support search, playback and backup by event;
- Support all channel image display on one screen at same time, support 4 channels' image display by mainstream, and 4 channels playback;
- Support monitor PTZ on preview mode
- Offer CMS for free

Model Number	Dynacom DN6108P	
Operating System	Embedded LINUX operating system	
Image Code Control	Image code quality adjustable, variable bitstream and constant bitstream optional	
Dual Stream	Each channel can set main stream and sub stream	
Video Standard	1080P(1920×1080)30fps/960P/(1280×960)/720P(1280×720)30fps	
Monitoring Image Quality	1080P(1920×1080) / 960P/(1280×960)/720P(1280×720)	
Image Motion Detection	Each screen can set mutiple detection areas and set 6-level sensitivity (IPC Support)	
Recording Playback Quality	4ch playback in 4ch 720 mode; 1ch 1080P playback in 4ch 960P/1080P model	
Region Cover	Every channel can set 4 cover regions (IPC Support)	
Recording Mode	Support manual , auto, dynamic detection, alarm trigger record mode(Partly needs IPC Support)	
Backup Way	Support U disk, USB mobile HDD, USB DVD-RW, network storage and backup	
Operation Way	Mouse	
Local Login	User name and password	
Recording Storage	Local HDD, network	
External Ports	Video Input	① 8x(1280*720) +sub[640*360]+1Ref.+4Play 8ch 1.0MP IP Camera
		② 8x(1280*960)+sub[640*480]+4Ref.+1Play 8ch 1.3MP IP Camera
		③ 8x(1280*960)+sub[720*576]+2Ref.+1Play 8ch 1.3MP IP Camera
		④ 8x(1920*1080)+sub[640*480]+2Ref.+1Play 8ch 2.0MP IP Camera
		⑤ 8x(1920*1080)+sub[720*576]+1Ref.+1Play 8ch 2.0MP IP Camera
	Audio Input	8ch network audio input
	Video Output	1ch VGA+1ch HDMI
Audio Output	1ch RCA Output	
Network Port	9 RJ45, 100M LAN port, data transferring and power supply both by network cable	
USB Port	3 USB 2.0 ports	
Wireless Port	3G, WIFI	
HDD	HDD Port	1 SATA HDD Port
	MAX Capacity	Each port supports MAX 4TB HDD
Mobile Surveillance	Support(iPhone, Windows Mobile, BlackBerry, Symbian, Android) smart phone	
Power Supply	DC48V 2.5A	
Power Consumption	≤115W (without HDD)	
Working Temperature	-10°C~ + 55°C	
Working Humidity	10%-90%	
Dimension	Equipment : 260mm×220mm×43mm, Packing : 355mm×255mm×88.5mm	
Weight(without HDD)	N.W. : 1.7Kg ; With packing : 2.6Kg	
Outside Carton	10 pcs/carton. 525mm×455mm×365mm ; Weight : 27 Kg	
Installation Way	Desktop Installation	