

## Dynacom DN6108 SERIES 8CH 960P/8CH 1080P 1HDD NVR



- P2P cloud service, including cloud connecting, cloud monitoring, cloud transmitting to access IPC and NVR at any time and any place
- Support Onvif protocol, support High profile S, High profile G, compatible with different IP camera that based on Onvif, RTSP standard
- Support megapixel HD network video preview, storage and playback;
- Support search, playback and backup by event;
- Support all channel image display on one screen at same time, support 4 channels' image display by mainstream, and 4 channels playback;
- Support monitor PTZ on preview mode
- Offer CMS for free

<b>Model Number</b>	<b>Dynacom DN6108</b>	
<b>Operating System</b>	Embedded LINUX operating system	
<b>Image Code Control</b>	Image code quality adjustable, variable bitstream and constant bitstream optional	
<b>Dual Stream</b>	Each channel can set main stream and sub stream	
<b>Video Standard</b>	1080P(1920×1080)30fps/960P/(1280×960)/720P(1280×720)30fps	
<b>Monitoring Image Quality</b>	1080P(1920×1080) / 960P/(1280×960)/720P(1280×720)	
<b>Image Motion Detection</b>	Each screen can set multiple detection areas and set 6-level sensitivity (IPC Support)	
<b>Recording Playback Quality</b>	4ch 720P playback in 8ch 720P mode;1ch 1080P playback in 8ch 1080P mode	
<b>Region Cover</b>	Every channel can set 4 cover regions (IPC Support)	
<b>Recording Mode</b>	Support manual , auto, dynamic detection, alarm trigger record mode(Partly needs IPC Support)	
<b>Backup Way</b>	Support U disk, USB mobile HDD, USB DVD-RW. network storage and backup	
<b>Operation Way</b>	Mouse	
<b>Local Login</b>	User name and password	
<b>Recording Storage</b>	Local HDD, network	
<b>External Ports</b>	<b>Video Input</b>	① 8×(1280*720)+sub[640*360]+1Ref.+4Play 8CH 1.0MP IP Camera
		② 8×(1280*960)+sub[640*480]+4Ref.+1Play 8CH 1.3MP IP Camera
		③ 8×(1280*960)+sub[720*576]+2Ref.+1Play 8CH 1.3MP IP Camera
		④ 8×(1920*1080)+sub[720*576]+1Ref.+1Play 8CH 2.0MP IP Camera
	<b>Audio Input</b>	4ch network audio input
	<b>Video Output</b>	1ch VGA+1ch HDMI
	<b>Audio Output</b>	1ch RCA output
<b>Network Port</b>	1 RJ45,10M/100M self-adaptive LAN port	
<b>USB Port</b>	3 USB 2.0 ports(one on front panel, two on rear panel)	
<b>Wireless Port</b>	3G, WIFI	
<b>HDD</b>	<b>HDD Port</b>	1 SATA HDD Port
	<b>MAX Capacity</b>	Each port supports MAX 4TB HDD
<b>Mobile Surveillance</b>	Support( iPhone, Windows Mobile, BlackBerry, Symbian, Android) smart phone	
<b>Power Supply</b>	12V2.6A	
<b>Power Consumption</b>	≤25W (without HDD)	
<b>Working Temperature</b>	-10°C ~ +55°C	
<b>Working Humidity</b>	10%-90%	
<b>Dimension</b>	Equipment : 260mm×220mm×43mm, Packing : 355mm×255mm×88.5mm	
<b>Weight(without HDD)</b>	N.W. : 1.5Kg ; With packing : 2.4Kg	
<b>Outside Carton</b>	10 pcs/carton. 525mm×455mm×365mm ; Weight : 25 Kg	
<b>Installation Way</b>	Desktop Installation	