

## DynaCom DN6432F , 32ch NVR, 4\*SATA



- H.265 video compression
- Third-party IP cameras supported with ONVIF conformance
- Support PnP for easy IPC discovery and usage
- Up to 8 Megapixels resolution recording, storage and playback
- Support 2-ch HDMI, 1-ch VGA, HDMI2 is up to 4K(3840x2160) resolution
- Up to 16 channels synchronously playback
- Support instant playback
- Support corridor mode
- 4 SATA HDDs up to 24TB

<b>Model No.</b>	<b>DN6432F</b>
<b>Video/Audio Input</b>	
IP Video Input	32 CH
Two-way Audio Input	1 CH, RCA (2.0 Vp-p, 1kΩ)
<b>Network</b>	
Incoming bandwidth	320Mbps
Outgoing bandwidth	320Mbps
Remote connection	16
Network Protocols	IPv4/IPv6, TCP/IP, HTTP, UPNP, RTSP, UDP, SMTP, NTP, FTP, DHCP, DNS, DDNS, PPPoE, DDNS
<b>Video/Audio Output</b>	
HDMI Output	2
VGA Output	1
CVBS Output	/
Audio Output	1 CH, RCA
<b>Decoding</b>	
Live View/Playback Resolution	8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/VGA/D1/CIF
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/VGA/D1/CIF
Synchronous Playback	16 CH
	32 x 720P@25, 16 x 720P@30, 16 x 1080P@25, 7 x 4MP@30, 5 x 5MP@30, 4 x 6MP@30, 4 x 4K@25
<b>Hard Disk</b>	
SATA	4
Capacity	Up to 6TB for each disk
<b>External Interface</b>	
Network Interface	2RJ-45 10/100/1000Mbps self-adaptive Ethernet interface
Serial Interface	1 RS-232, 1 RS-485
USB Interface	2 USB2.0 + 1 USB3.0
eSATA Interface	/
Alarm In	16
Alarm Out	4
<b>POE</b>	
Interface	NA
Max. Power	/
Supported Standard	NA
<b>General</b>	
Power Supply	12V, DC
Consumption	≤12W (Without Disk)
Working Temperature	-10°C ~ 55°C (14°F ~ 131°F)
Working Humidity	10% ~ 90%
Dimensions	44.0mm × 440.0mm × 344.0mm (1.73" × 17.32" × 13.54"), 1U
Weight(without HDD)	≤3.2KG

