

Dynacom WQ1001 1 M IR LED Bullet Camera



- 1 Megapixel real time
- Highest resolution 1280×960
- 20-30M(2xIR III LEDs, 36xΦ5 LEDs optional)
- 3.6mm Megapiksel Lens
- Built-in IR-CUT filter
- H.264 Video Encoding
- IP66, Lighting-proof, DC12V

Model No.	WQ1001
CAMERA	
Sensor	1/3"Progressive scan CMOS
Min. Illumination	0.1Lux/F1.4
Electronic Shutter	Auto/Manual (1/25~1/10000)
Day/Night	Auto/B/W/Color/EXT ICR switching
Video Parameter	DWDR, Mirror, 3D Noise reduction, Sharpness/Lightness adjustable
IR Distance	20-30M(2xIR III LEDs, 36xΦ5 LEDs optional)
Lens	3.6mm Megapiksel
Lens Interface Type	M12
AUDIO/VIDEO COMPRESSION	
Video Compression	H.264
Encoding	Dual-stream; Main stream: 1280×960 25fps/30fps Sub Stream: 720×576 25fps/720×480 30fps
Effective Pixels	1280×960
Encoding System	Constant bit rate, Variable bit rate optional
Video Bit Rate	16Kbps-8000Kbps
Stream Type	Complex stream/Video stream
Audio Compression	G.711A
Audio Bit rate	64Kbps
NETWORK FUNCTION	
Motion Detection	Can set a single detection zone, multi-level sensitivity can be set
Video Mask	Support 4 areas to mask
Screen Capture	Support JPEG format, max. resolution based on encoding resolution
Password Protection	Supported
Character Display	Supported (Channel name,Date)
Alarm Function	Video loss, Network disconnect, Tampering alarm, Storage exception
Mobile Surveillance	Apple, Android
Protocol	TCP/IP,UDP,HTTP,DHCP,RTP/RTSP,DNS,DDNS,NTP,PPPOE,UPNP,SMTP
Port Protocol	i8S, ONVIF
INTERFACE	
Analog Video Output	1CH CVBS analog video output
Network Interface	RJ45 10M/100M adaptive
GENERAL	
Operating Conditions	-10°C ~ 55°C/0% -90%
IP Grade	IP66
Power Supply	DC12V /POE optional
Power Consumption	<5W (without IR LED)
Dimensions	65(W)*63(H)*167(L)mm
Weight	About 200g



WDR



1 MP

