

Dynacom WQ4NM 4M IR LED Dome Camera



- 4 Megapixel full HD real time
- Highest resolution 2592*1520
- 8pcs * \varnothing 10mm IR Led
- IR Range 20mt
- 2.8 -12mm Lens
- H.264 Compression
- Support Dual-Stream
- Support ONVIF protocol
- Support RTSP browse video in real time

| | |
|----------------------------|---|
| Model No. | WQ4NM |
| CAMERA | |
| Sensor / Resolution | 1.3" OV / 2592*1520 |
| Min. illumination | 0.1Lux @ F1.2 (Color) (0 Lux IR LED On) |
| Lens | 2.8-12mm Lens |
| Video Output | Main stream:2592*1520 Deputy stream:704*576 |
| Compression | H.264 Video Code, Support dual-stream |
| IR Distance | 20mt (8 pcs) |
| Bit Rate (CBR/VBR) | Support 32k-8m adjustable,1-30 fps frame rate adjustable |
| Multi- Streaming | User setting of Stream 1/2 at supported Resolutions |
| Gain control | Auto |
| Text Overlay | Time / Date / Camera / Custom OSD |
| Network Port | One RJ45 Ethernet interface, 10M/100M self-adaption |
| Standard protocol | Onvif 2.4 |
| Network Protocols | TCP/UDP/HTTP/MULTICAST/UPnP/NTP/RTSP/Onvif |
| SD Card | Max. 64 GB |
| 3GWireless Transmission | NO |
| WIFI Wireless Transmission | NO |
| Mobile phone monitor | Support mobile phone monitor (Iphone, Windows Mobile, Android) |
| Operation | Support Web setting,OSD,real-time video transmission,support motive detection and IO alarm linkage for front end shortage/Capture/playback/download |
| Function | Support Central remind and image linkage after motive detection and IO alarm linkage,support MJPEG capture,Support unit clint-side remote management software Easy7 platform system apply |
| Audio | Support |
| Alarm | Optional |
| Power Supply | DC9V~12V,<3W |
| Working Temperature | -35°C~65°C |
| Protection Rate | ESD 1kv |



WDR



4 MP

