

Dynacom WQ8M12

Mini Fisheye Camera

12M pixel
 12MP 4072*3046
 12MP High-definition Panoramic Lens 1.77mm
 Built-in IR-CUT.Low power consumption
 Micro SD 128GB support
 H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG
 Support Multiple-Stream
 Support ONVIF protocol



CAMERA	
Model	WQ8M12
Case	Metal, Dome
Image Sensor	1/1.7" SONY Low Illumination CMOS Sensor
Max Resolution	4072x3046
Min. illumination	0.01Lux @ F1.2 (Color) (0 Lux IR LED On)
Day / Night	Day / Night with ICR Filter.
IR Leds	3pcs* Φ , IR Range: 20M
Lens	1.77mm Board Lens
Lens Pixels	12MP High-definition Panoramic Lens
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Video Output	Main stream:4000*3000@20fps
	Sub stream:720*720@30fps
	Tri stream:512*512@30fps
PARAMETERS	
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
Bit Rate (CBR/VBR)	32Kbps-16Mbps continuously adjustable, support CBR/VBR
Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
NETWORK	
Network Port	One RJ45 Ethernet interface, 10M/100M self-adaption
Standard protocol	Onvif 2.4
Network Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
Mobile phone monitor	Support mobile phone monitor (iPhone, iPad, Android, Android Pad)
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
CONNECTOR	
Audio*	2-way audio(3.5mm audio interface)
IO function port*	Reset (Optional)
Alarm in/output*	1* Alarm input port/1*Alarm output port
SD Card	Micro SD 128GB
GENERAL	
power	DC12V / PoE (802.3af) power input port. 5w power
Working Temperature	-20°C ~ +60°C RH95% Max
Housing	IP66
Product Dimensions	Φ 120 x 49(H) mm
Weight	500g