

## Dynacom WQ920ZV 2.1M IR LED Bullet Camera



- 2Mpixelfullreal time optional
- Highest resolution 1920\*1080
- IR Leds:42pcs\* 5mm, IR Range: 40M
- 2.8-12mm Motorized Lens
- Built-in IR-CUT, Low power consumption
- H.264 Video Coding
- Support Dual-Stream / ONVIF agreement / RTSP browse video in

### Functions

**defog** : get higher image contrast by filtering , better depth of field , clearer picture

**multi-stream technology** : Front device can output a variety of different streams to different devices for viewing

Model No.	WQ920ZV
<b>CAMERA</b>	
Sensor	1/ 2.8" Sony Progressive scan CMOS Min.
Illumination	Color 0.1Lux/F1.2; B/W 0.00Lux/F1.2
Electronic Shutter	Auto/Manual ( 1/25~1/10000 )
Day/Night	True Day / Night with ICR Filter.
Video Parameter	DWDR, Mirror, 3D Noise reduction, Sharpness/Lightness adjustable
IR Distance	40M( 42xIR III LEDs )
Lens	2.8-12mm Motorized megapixel lens
Lens Interface Type	M12
<b>AUDIO/VIDEO COMPRESSION</b>	
Video Compression	H.264 Video Code, Support dual-stream
Encoding	Dual-stream; Main stream: 1920×1080 25fps/30fps Sub Stream: 720×576 25fps/720×480 30fps
Effective Pixels	1920×1080
Encoding System	Constant bit rate, Variable bit rate optional
Video Bit Rate	Support 32k-16m adjustable, 1-30 fps frame rate adjustable
Stream Type	Complex stream/Video stream
Audio Compression	G.711A, G.711U, G.726
Recording	SD Card ( up to 64GB )
<b>NETWORK FUNCTION</b>	
Motion Detection	Can set a single detection zone, multi-level sensitivity can be set
Video Mask	Support 4 areas to mask
Screen Capture	Support JPEG format, max. resolution based on encoding resolution
Password Protection	Supported
Character Display	Supported ( Channel name, Date )
Alarm Function	Video loss, Network disconnect, Tampering alarm, Storage exception
Mobile Surveillance	Apple iOS, Android
Protocol	TCP/UDP/HTTP/MULTICAST/UPnP/NTP/RTSP/Onvif
Port Protocol	ONVIF
<b>INTERFACE</b>	
Audio	Line in / Line out
Network Interface	RJ45 10M/100M adaptive
<b>GENERAL</b>	
Operating Conditions	-30°C ~ 55°C/0% -90%
IP Grade	IP66
Power Supply	DC12V /PoE optional
Power Consumption	<5W (without IR LED)
Dimensions	Ø 90 x 270 mm ( Ø 3.3 x 7.6 in.) w/ Sunshield
Weight	About 940g



WDR



2MP



Mobile phone monitor  
(Android/iPhone  
/Windows Mobile)