



## **Dynacom** WQ940A 4M IR LED Bullet Camera

- 4 Megapixel full HD real time
- Highest resolution 2592\*1520
- IR Distance 60mt (72 pcs)
- 2.8 -12mm Lens
- H.264 Compression
- Support Dual-Stream
- Support ONVIF protocol
- Support RTSP browse video in real time

| Model No.                  | WQ940A  |
|----------------------------|---|
| CAMERA                     |   |
| Sensor / Resolution        | 1.3" OV / 2592*1520   |
| Min. illumination          | 0.1Lux @ F1.2 (Color) (0 Lux IR LED On)   |
| Lens                       | 2.8-12mm Lens   |
| Video Output               | Main stream:2592*1520   |
|                            | Deputy stream:704*576   |
| Compression                | H.264 Video Code, Support dual-stream   |
| IR Distance                | 60mt ( 72 pcs )   |
| Bit Rate (CBR/VBR)         | Support 32k-8m adjustable,1-30 fps frame rate adjustable  |
| Multi- Streaming           | User setting of Stream 1/2 at supported Resolutions   |
| Gain control               | Auto  |
| Text Overlay               | Time / Date / Camera / Custom OSD   |
| Network Port               | One RJ45 Ethernet interface, 10M/100M self-adaption   |
| Standard protocol          | Onvif 2.4   |
| Network Protocols          | TCP/UDP/HTTP/MULTICAST/UPnP/NTP/RTSP/Onvif  |
| SD Card                    | Max. 64 GB  |
| 3GWireless Transmission    | NO  |
| WIFI Wireless Transmission | NO  |
| Mobile phone monitor       | Support mobile phone monitor ( Iphone, Windows Mobile, Android)   |
| Operation                  | Support Web setting,OSD,real-time video transmission,support motive detection and IO alarm linkage for front end shortage/Capture/playback/download   |
| Function                   | Support Central remind and image linkage after motive detection and IO alarm linkage, support MJPEG capture, Support unit clint-side romote management software Easy7 platform system apply |
| Audio                      | Support   |
| Alarm                      | Optional  |
| Power Supply               | DC9V~12V,<3W  |
| Working Temperature        | -35°C∼65°C  |
| Protection Rate            | ESD 1kv   |



WDR



4 MP





