

EV6552R IP Camera

H.264 Mini IP Dome Camera



H.264

Audio

PoE

Vandal Proof

Features

- 1/4" Ultra Low-Light CMOS
- 3.6mm, F1.9 Fixed IRIS Lens
- Color Mode @ 0.1 Lux Minimum Illumination
- 640 X 480 VGA Resolution
- H.264, M-JPEG, MPEG-4 Video Compression Format Selectable
- 30fps (NTSC) / 25fps (PAL) @ D1 Resolution
- Simultaneous Dual Streams Controllable Frame Rate and Bandwidth CBR/VBR
- Intelligent Video and External Input Intelligent Video
- Pre-and Post Alarm Buffer up to 10-sec
- Vandal-proof (Lens holder Pan: 0-90° / Tilt: +/-10 / Rotation+/- 10)
- 12V DC / 1A Power Supply

Specifications

	Model	EV6552R	EV6552RP	
Camera	Image Sensor	1/4" Ultra Low-Light CMOS		
	Lens	3.6mm, F1.9 Fixed IRIS		
	Minimum Illumination	Color Mode @ 0.1 Lux		
	Shutter time	1/60 s to 1/32000 Selectable		
	Number of Effective Pixels (HxV)	640 x 480		
	Auto Iris	N/A		
	Sync System	N/A		
	Resolution	640 X 480 VGA		
	S/N Ratio	45dB		
	Video Compression	H.264, M-JPEG, MPEG-4 Format Selectable		
Image Size	VGA(640x480), QVGA(320x240), QQVGA(160x120)			
Video / Audio	Frame Rate	30fps VGA Resolution		
	Video Streaming	Simultaneous Dual Streams with Controllable Frame Rate and Bandwidth		
	Day / Night	N/A		
	Image Settings	Compression, Brightness, Contrast, Saturation, Mirroring, Flip, AEC, AWB, AGC, AES, Fixed Gain, Lighting Freq.		
	Bit Rate	M-JPEG: 5 Video Quality Level Selectable: MPEG-4/H.264 : 64K-4Mbps		
	Video Output	N/A		
	Audio	Audio In/Out : ADPCM Built-in Mic		
Network	Security	Password Protection, IP Address Filtering, User Access Privilege		
	Protocols	TCP/IP, UDP, DHCP, PPPoE, HTTP, DNS, DynDNS, NTP, FTP, SMTP, UDP, RTP, RTSP, 3GPP, UPnP, IPv4, SAMBA client (NAS)		
System Integration	Application Programming Interface	EtroSDK™ 3.0		
	Intelligent Video	Video Motion Detection		
	Alarm Trigger	Periodical Timer, Intelligent video and external input		
	Alarm Events	Intelligent Video, File Upload via FTP and E-mail, Notification via E-mail, External Output Activation, File Recording to Remote FTP or NAS		
	Video Buffer	Pre-and Post Alarm Buffer up to 10-sec		
General	Configuration	EtroScan™ Utility, Web UI		
	Web Browser	Microsoft Internet Explorer 6.0, or Above		
	Casing	Vandal-proof (Lens holder Pan: 0-90° / Tilt: +/-10 / Rotation+/- 10)		
	Dimension	114(Ø) X 39(H) mm		
	Processor and Memory	ARM9 Base SoC, 128MB RAM, 16MB Flash		
	Power	12V DC / 1A	12V DC / 1A, PoE	
	Connectors	RJ-45 for 10BASE-T/100 BASE-TX, DC Jack , Reset, Audio Out, DI/DO		
	Operating Conditions	- 10 °C ~ 50 °C (14 °F ~ 122 °F) Humidity: 20% ~ 80% RH		
	Power over Ethernet	N/A	802.3af standard A/B compliant	
	Wireless	N/A		
	Approvals	CE, LVD, FCC, EN50155, RoHS		
Weight	235g	247g		
Included Accessories	OIG, Power Adapter, CD-ROM (User Manual, Free Bundle NVR)			

Dimensions

