

# EV8180U

## Full HD Box Type IP Camera



Full HD

H.264

Audio

PoE

Day&Night

SDHC



AC/DC power input

Multi ROI

### Features

- 1/2.7" 1080P CMOS
- 1lux @ F1.2 Minimum Illumination
- H.264 / MPEG-4/ M-JPEG Dual Streams Simultaneously
- Full HD Resolution at 30 fps
- 4 (ROI Support) with independent streaming
- Day / Night Mode, Built-in ICR
- Two-way Audio, Built-in Microphone
- SD/ DI/ DO RS422/RS485/RS232
- 802.3af standard A/B compliant PoE
- Wireless support

### Dimensions



1. DC IRIS adaptor
2. I/O cable port
3. SD card slot
4. USB for External WiFi dongle
5. RJ45 network port
6. Power port (8-25V AC or DC)
7. Line in
8. Line out

Figure. Rear Panel

### Specifications

|                    | Model                          | EV8180U   |
|--------------------|--------------------------------|---|
| Camera             | Image Sensor                   | 1/2.7" HD-1080P CMOS  |
|                    | Num. of Effective Pixels (HxV) | 1920 x 1080   |
|                    | Lens                           | CS-mounted MP Lens Changeable   |
|                    | Minimum Illumination           | 1lux @ F1.2   |
|                    | Shutter Time                   | 1/50 s to 1/12000 Selectable  |
|                    | Auto IRIS                      | DC Drive  |
|                    | S/N Ratio                      | More than 38.1dB  |
|                    | Day/Night                      | YES, built-in ICR   |
|                    | Video / Audio                  | Video Compression   |
| MJPEG              |                                | 30fps @ 1920x1080 HDTV-1080P Resolution   |
| MPEG4              |                                | 30fps @ 1920x1080 HDTV-1080P Resolution   |
| H.264              |                                | 30fps @ 1920x1080 HDTV-1080P Resolution   |
| Video Streaming    |                                | Multiple Stream : support up to 4 independent ROI (Region of Interest), controllable Frame Rate and Bandwidth CBR/VBR                           |
| Bit-rate           |                                | M-JPEG: 5 Video Quality Level Selectable; MPEG-4/H.264 : 128K~16Mbps  |
| Video Output       |                                | SDTV - Composite video / HDTV - Component (Y/Pb/Pr) video   |
| Image Setting      |                                | Compression, Brightness, Contrast, Mirroring, Sharpness, AWB, AES, AGC, BLC, Day/Night Mode, 4 Privacy Mask Regions                             |
| Audio Compression  |                                | ADPCM / AAC   |
| Audio Input        |                                | Built-in Microphone / Line In x1  |
| Audio Output       | Line Out x1                    |   |
| Network            | Security                       | Password Protection, IP Address Filtering, User Access Privilege  |
|                    | Network Protocol               | TCP/IP, UDP, DHCP, PPPoE, HTTP, HTTPS, DNS, DynDNS, NTP, FTP, SMTP, UDP, RTP, RTSP, RTCP, 3GPP, UPnP, IPv4/v6, SAMBA client (NAS)               |
| System Integration | App. Integration Interface     | CGI / ONVIF Support   |
|                    | Intelligent Video              | Video Motion Detection / Face Detection   |
|                    | Alarm Trigger                  | Intelligent Video and external digital input  |
|                    | Alarm Event                    | Intelligent Video, File Upload via FTP and E-mail, Notification via E-mail, External Output Activation, File Recording to SD Card or Remote NAS |
|                    | Video Buffer                   | 100MB Max   |
| General            | Configuration                  | EtroScan™ Utility, Web UI   |
|                    | Web Browser                    | IE 6.0 or above   |
|                    | Local Storage                  | SD/SDHC Card support  |
|                    | Casing                         | Metal (Aluminum)  |
|                    | Dimension                      | 76(W) X 58(H)X 109(D) mm  |
|                    | Weight                         | 486g  |
|                    | Processor and Memory           | ARM9 Base SoC, 256MB RAM, 128MB Flash   |
|                    | Power                          | DC: 8~25V / AC: 8~25V / Power over Ethernet   |
|                    | I/O Connector                  | Refer to figure of rear panel   |
|                    | Failover                       | SD/SDHC auto-recovery / Reset   |
|                    | Operation Conditions           | 0 °C ~ 50 °C (32 °F ~ 122 °F) Humidity: 20% ~ 80% RH  |
|                    | Power over Ethernet            | 802.3af standard A/B compliant  |
|                    | Wireless Support               | Yes, External USB Dongle  |
|                    | Included Accessories           | Power Adaptor Power cable I/O cable CD-ROM Stand  |
|                    | Approvals                      | FCC Part15 SubpartB/ CN EN55022 ClassB, EN55024/ LVD/ RoHS  |
|                    | IR Range                       | N/A   |
|                    | Number of IR LED               | N/A   |
| IR Angle           | N/A                            |   |
| IR Wavelength      | N/A                            |   |