

EAN900

1.3 Megapixel Day/Night IP Box Camera





Features

- H.264/PJEG-4/MJPEG digital signal output with up 15 FPS at 1280x1024
- H.264/MPEG4/MJPEG output for simultaneous live monitoring and high resolution recording
- 12VDC and Power Over Ethernet (PoE) IEEE 802.3af
- BNC test monitor output for the convenience of quick focus and diagnostics right at the camera site
- Built-in SD memory card slot for local storage (supports SDHC)
- Smart Wizard settings for various event & schedule recordings
















Specifications

Part Number	EAN900
Pickup Device	1/3" Progressive scan CMOS 1.3 Megapixel
Effective Pixels	1280 (H) x 1024 (V)
Sensitivity	0.5 Lux/F=1.2
Day/Night	Yes with ICR module
Lens	Optional C/CS mount, manual/DD control supported
Video Output	BNC socket, composite 1.0Vp-p/75 ohm
Video Resolution	NTSC : SXGA (1280X1024), SWXGA (1280 X960), 720P (1280x720), VGA (640x480)
Video Compression	H.264/MPEG4/MJPEG
Video Quality	8 levels adjustable
Frame Rate	up to 15 FPS in 1280x1024
Interface	10Base-T/100Base-TX auto-negotiation, FJ-45 socket. Supports MDI/MDI-X auto cross function
Supported Protocols	HTTP, TCP/IP, FTP, SMTP, DHCP, DNS, DDNS, NTP
Bandwidth Control	Min. 64 k bit per sec. adjustable
Max Client Limit	32 clients simultaneously
Power Over Ethernet	Yes (PoE 802.3af)
Alarm Input	1
Alarm Output	1
Audio In/Out	Built-in mic, and option 3.5mm mono line input/ line out
Operation Mode	Two-way audio
Event Trigger	Alarm Input, Manual Trigger, Motion Detection and Schedule Recording
Notification	Trigger alarm output, email notification, upload video to FTP, record video to SD card, record video to PC and network alarm
Pre/Post Alarm Buffer	48MB RAM reserved for pre-alarm (record up to 120 sec.)
SD Card	Supports SD and SDHC for local storage
Power Supply	12VDC & PoE
Power Consumption	4.5W max. (12VDC)
Weight	1.21 lbs
Dimension	5.35" x 2.72" 2.22"
Operating Temp	0°C- 40°C/ 32°F - 104°F
Humidity	<90% not condensing
Certifications	CE, FCC, RoHS

Dimensions: mm/in



Ordering Info

Note: Lens Sold Separately

