EverFocus®

EVS410



Features


- · High quality H.264/ and MJPEG
- Dual stream (per channel) for simultaneous live monitoring and high resolution recording
- Smart Wizard setting for varies event and schedule recording
- Built-in SD memory card slot for local storage
- Supports SD high capacity
- · Space saving with ultra compact design

				SD
		~ ~~	-₩	Card
PTZ Control	Web Viewer	Smart Event Wizard	Two-Way Audio	Slot

Specifications

opeenie			
Channels	4		
Recording/Playback Rate	up to 30 FPS per channel		
Total Recording Rate	up to 120FPS (4 channels up to 30 FPS each)		
Recording Resolution	4CIF, VGA, CIF, QVGA, QCIF		
Compression Supported	H.264/M-JPEG		
Compression Method	IMA ADPCM (Pulse Code Modulation)		
Audio	Two-way audio		
Video Storage (Excludes O/S and system software on HDD 1)	SD card interface for local storage, supports SDHC		
Network Interface	10Base-T/100Base-TX auto-negotiation, RJ-45 socket. Supports		
	MDI/MDI-X auto crossover function.		
Max Client Limit	32 simultaneous clients		
Pre/Post Alarm Buffer	Unsure, as no mention is technical specs, advisable to leave it as ""		
Alarm I/O	4 in/ 2 out		
Event Trigger	Alarm Input, Manual Trigger, Motion Detection and Schedule		
	Recording		
Notification	Trigger alarm output, send email notification, upload video to FTP, record video to SD card, record video to PC and network alarm		
PTZ	Supports PTZ control		
Remote Video Access Method	Internet Explorer 8		
Power	12VDC		
Power Consumption	36W (12VDC)		
Temperature	0°C ~50°C / 32°F~122°F		
Housing	Compact		
Dimensions	5.2"(W) x 1.5"(H) x 6.5" (D)		
Weight	1.47 lbs		
Certifications	CE, FCC		

Dimensions: mm/in



Ordering Info

EVS410: 4 Ch., Video Server Encoder