

# EZN468M / EZN468ME

4-Megapixel IR, Motorized, Outdoor Bullet Network Camera

### Onvie




























### **Features**

- 4M CMOS sensor
- Motorized 2.8-12mm lens to capture the desired field of view
- Digital Wide Dynamic Range Function
- Provides True Day/Night functionality with automatic IR filter operation
- Extended IR range of up to 30m / 100ft. with 3 High Power IR LEDs (Depending on scene IR reflectivity)
- Multi-streaming from H.265 / H.264
- Supports Motion Detection & Email Notification
- Weather proof IP66-rated
- The flexible angle viewing with its 3-Axis rotation design allows wall or ceiling mounting
- Supports live monitoring of video from mobile devices via MobileFocus / MobileFocus Plus apps (iOS and Android)
- Supports Power over Ethernet / 12VDC
- Two-way audio\*
- Supports Alarm I/O\*
- Supports RS-485\*
- EverFocus Genie XMS CMS
- ONVIF profile S compliant
- Supports Micro SD card

### EZN468M




### EZN468M Economy



Cable Options	EZN468M	EZN468M Economy
Alarm In (with Terminal Block)	Yes	-
Alarm Out / RS-485 (reserved Terminal Block)	Yes	-
Audio In (Red)	Yes	-
Audio Out (White)	Yes	-
Video Out (BNC)	Yes	-
LAN/PoE	Yes	Yes
12VDC	Yes	Yes
Reset Button (with a dust-proof cap)	Yes	Yes





### **Optional Accessories**

Пп	ncti	ion	Box
Ju	HCC	IOH	DUA

#### **PBOX-A30 W-4**



#### Suitable for **EZN468M**

139mm x 33.5mm / 5.47" x 1.32" (D) x (H)

High-strength Aluminum for better protection against damage.

Apple White spray-painted surface to protect the bracket from corrosion and rust.

#### PBOX-A32E-4



#### Suitable for **EZN468M Economy**

119.2mmx38mm / 4.7" x 1.5" (D) x (H)

High-strength Aluminum for better protection against damage.

Apple White spray-painted surface to protect the bracket from corrosion and rust.

#### **IP Sidekick**

#### IP Sidekick - ESK1000



EverFocus Sidekick is a rechargeable battery powered WiFi access point with a 30 watt PoE port. After mounting the camera, the installer can power the camera with the Sidekick device. A tablet/smart phone installed with EF Sidekick App can be used to log in and test/view the camera and make adjustments right at the camera. For more details please refer to the IP Sidekick – *ESK1000 User's Manual*.

#### PoE Switch

#### EverFocus 5 / 8 / 16 / 24 Ports PoE Switch



5 Ports: EPOE 05 8 Ports: EPOE 08

16 Ports: EPO16E / EPOE16 24 Ports: EPOE24 / EPOE24E

## **Specification**

Model No.	EZN468M / EZN468M Economy		
Pickup Device	4M CMOS sensor	Stream Type	Complex stream / Video stream
Lens	Motorized 2.8-12mm lens	Image Settings	Contrast, Brightness, Saturation, Sharpness, Mirroring of Images
Camera Angle Adjustment	Horizontal 360°, Vertical 90°	Intelligent Alarm	Video Loss, Network Anomaly, Tampering Alarm, Storage Exception, Motion Detection
Minimum Illumination	Color: 0.5Lux @F1.4 B/W: 0.2Lux @F1.4	Event Trigger	Motion Detection
Day/Night	True Day/Night with ICR	Notification	Email Notification
Iris	Fixed Iris	Password Protection	Support
Electronic shutter	Auto / Manual (1/25 ~ 1/10,000), FLK	Storage	Micro SD / SDHC / SDXC slot (Max. 128G, up to class 10)
Video Compression	H.265 / H.264	IR LED	3 (High Power IR LEDs)
Max. Video Resolution	2592 x 1520	IR Distance	30m / 100ft.
Frame Rate	25fps / 30fps	Power Supply	12VDC
S/N Ratio	≥ 35db (AGC OFF)	Power over Ethernet	PoE IEEE802.3af (Class 3)
AGC	Yes	Max. Power Consumption	12VDC 7.4W / PoE 8.2W
AWB	Yes	Humidity	0% ~ 90% not condensing
D-WDR	Yes	Operating Temperature	-10°C ~ 50°C / 14°F ~ 122°F
3DNR	Yes	Dimensions (L) x (Φ)	263 x 93mm / 10.35" x 3.66"
Interface	RJ-45 10M/100M adaptive	Weather Resistance	IP66
Supported Protocols	TCP/IP, UDP, HTTP, DHCP, RTSP, DDNS, NTP, PPPOE, UPNP, SMTP, ONVIF	Weight	957g / 2.11lb
Reset Button	Yes	Certificates	CE, FCC, RoHS
	The state of the s	t .	i e e e e e e e e e e e e e e e e e e e

<sup>\*</sup>All images presented in this document are for example only. Product models may vary in different countries. Please visit EverFocus regional Websites for detailed ordering information.



<sup>\*</sup>Information contained in this document is subject to change without notice.