

## DS-2CD251PFW-I (W)(S) 1.3MP WDR Mini Dome Network Camera



- Up to 1.3 megapixel high resolution
- Dual video streams
- 2.8mm/4mm/6mm fixed lens
- 120dB Wide Dynamic Range
- 3D Digital Noise Reduction
- 3-axis adjustment
- Support on-board storage, up to 64GB
- DC12V & PoE
- Support H.264+
- Up to 10m IR range
- IP67 weather-proof protection
- IK08 vandal-proof protection
- -S: Built-in microphone, Audio Output, Alarm IO
- -W: Built-in Wi-Fi

### Camera Accessories



Wall mount  
DS-1272ZJ-120



Wall mount + Junction Box  
DS-1272ZJ-120B



Pendant mount  
DS-1271ZJ-120



Corner mount  
DS-1276ZJ



Vertical Pole mount  
DS-1275ZJ



Rain-proof Cap  
DS-1250ZJ



# DS-2CD251PFWD-I (W)(S) 1.3MP WDR Mini Dome Network Camera



## Specification

<b>Camera</b>	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	0.01Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Speed	1/3 s to 1/10,000 s
Lens	2.8mm, 4mm, 6mm @ F2.0 angle of view: 100°(2.8mm), 90°(4mm), 53.9°(6mm)
Lens Mount	M12
Day & Night	IR cut filter with auto switch
DNR	3D DNR
Wide Dynamic Range	120dB
Angle of adjustment	Pan: -30° ~ 30°, Tilt: 0 ~ 75°, Rotation: 0 ~ 360°
<b>Compression Standard</b>	
Video Compression	H.264 / MJPEG/H.264+
H.264 Type	Main Profile
Video Bit Rate	32 Kbps ~ 16 Mbps
Dual Streams	Support
Audio Compression	G.711/G.722.1/G.726/MP2L2 *only for -S models
Audio Bit rate	64Kbps(G.711) / 16Kbps(G.722.1) / 16Kbps(G.726) / 32-128Kbps(MP2L2) *only for -S models
<b>Image</b>	
Max. Resolution	1920 × 1080
Max Frame Rate	50Hz: Main stream: 25fps(1280×960), 25fps(1280×720) Sub stream: 25fps(352×288), 25fps(640×360) 60Hz: Main stream: 30fps(1280×960), 30fps(1280×720) Sub stream: 30fps(352×240), 30fps(640×360)
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser
BLC	Support, zone configurable
ROI Codec	Support
<b>Network</b>	
Network Storage	NAS (Support NFS, SMB/CIFS), ANR
Detection	Intrusion detection, Line crossing detection, Motion detection, Dynamic analysis
Alarm Trigger	Tampering alarm, Network disconnect, IP address conflict, Storage exception
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
General	One-key reset, Anti-Flicker, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering, Anonymous access
Standard	ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
<b>Interface</b>	
Communication Interface	1 RJ45 10M/100M Ethernet port
On-board storage	Built-in Micro SD/SDHC/SDXC slot, up to 128 GB
Alarm interface	1x alarm I/O *only for -S models
Audio interface	Built-in microphone and 1x audio output *only for -S models
Reset	Yes

# DS-2CD251PFWD-I (W)(S) 1.3MP WDR Mini Dome Network Camera



## Wi-Fi \* only for -W models

Wireless Standards	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	20/40MHz Support
Protocols	802.11b: CCK, QPSK, BPSK, 802.11g/n: OFDM
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
Transfer Rates	11b: 11Mbps, 11g: 54Mbps, 11n: up to 150Mbps
Wireless Range	50 meters *The performance varies based on actual environment.

## General

Operating Conditions	-30 °C ~ 60 °C (-22 °F ~ 140°F), Humidity 95% or less (non-condensing)
Power Supply	DC12V ±25%, PoE (802.3af Class3)
Power Consumption	Max. 5W
Material	Top Cover: Plastic ; Base: Metal
IR Range	Approx. 10 meters
Ingress Protection	IP67
Impact Protection	IEC60068-275Eh, 20J; EN50102, up to IK08
Dimensions	99.3 × 96.7 × 52.8 mm
Weight	600 g (1.32 lbs)

## Order Models

DS-2CD251PFWD-I, DS-2CD251PFWD-IS, DS-2CD251PFWD-IW, DS-2CD251PFWD-IWS,  
-S: Built-in Mic, Audio out, Alarm I/O, -W: Built-in Wi-Fi

## Dimensions

