

CDD123-04 / CDD123-08



Key Features:

- H.264 triplex real time DVR
- Graphical interface, easy to use
- Support USB mouse
- VGA 1280*1024, HDMI 1080 video out
- Strong log function supported
- Powerful remote configuration and maintenance function
- Express backup
- CMS available (T Series)

Technical Features

Model		CDD123-04	CDD123-08
Operating System		LINUX	
Operation Performance		Triplex Function, Simultaneous Record/Playback/Network	
Video Compression		H.264 Baseline Compression	
Live Display Speed		NTSC: 120fps@ D1, PAL: 100fps@ D1	NTSC: 240fps@ D1, PAL: 200fps@ D1
NTSC	CIF	120fps	240fps
	2 CIF	120fps	240fps
	D1	120fps	120fps
PAL	CIF	100fps	200fps
	2 CIF	100fps	200fps
	D1	100fps	100fps
Video Input		4 CH	8 CH
Video Output	HDMI		
	VGA	1280*1024	
	Main Monitor	2 Composite [BNC], VGA	
	Spot-Output	Yes	
	Loop-Output	No	
Screen Division	Live	1.4	1,4,6,8
	Playback	1.4	1,4,8
Audio	Compression		
	Audio Input	1 CH RCA	
	Input Level	2Vp-p,10K	
	Audio Output	1 CH RCA	
	Alarm Input / Output	NA	
Data Storage		SATA HDD x 1 (2TB)	
Media Support			
USB Port		2	
PTZ & Keyboard Control		RS-485	
Control Device		USB Mouse, Front Button, Remote Controller & Keyboard Controller	
Network		1 RJ45 10/100Mbps Ethernet Connector	
SEARCH&PLAYBACK			
Searching Methode		Search by Time	
Reverse Playback		Variable Playback	
Playback De Interlace		Instant playback mode for quick review	
Audio Play		Synchronized with Video	
SYSTEM			
PTZ		Supported most of PTZ protocol, Preset up to 255	
Motion Settings		Adjustable GRID	
Firmware Upgrade		Via USB device	
RECORD			
Recording Schedule		Manual/ Schedule/Sensor Trigger/Motion Detection /Power-on Auto Record	
NETWORK			
Network Support Type		LAN/DHCP/DDNS	
ENVIRONMENTAL			
Power		12V Adaptor	
Operating Temperature		5°C ~ +40°C	
Humidity		10 ~ 90% NC	
Monitoring Environment		CMS support, Web Viewer	
Dimension (mm)		343(W)x59(H)x223(D) mm	432(W)x90(H)x326(D) mm