

# CKV320-A60

## Key Features:

- 1/3" Sony Super HAD II CCD
- 2.8-12mm AVF Lens
- WDR (Wide Dynamic Range)
- Digital Zoom (x1 ~x10)
- Day&Night
- Waterproof (IP68)
- 600 TVL Resolution
- 0.1Lux F1.2/0.0001Lux (Sens-Up x256) (Color)
- 3DDNR (3D Digital Noise Reduction)
- LSC (Lens Shading Compenstaion)
- DIS (Digital Image Stabilizer)
- DC Iris Control
- ESC (Electronic Shutter Control)
- OSD Menu
- Privacy Masking
- Motion Detection
- Turkish Menu



Technical Features			
Sensor	1/3" Sony Super HAD CCD II	Automatic Gain Control (AGC)	Low, Middle, High Off Adjustable
Resolution	600 TVL	Day&Night	Auto (Day/Night), CDS, Color, B/W
Min. Illumination	0.1 Lux F1.2 (Color) / 0.0001Lux (B/W)	Sens-up	x256
Effective Pixels	PAL: 752(H) x 582(V) ; NTSC: 768(H) x 494(V)	DIS	On/Off
Scanning System	2:1 Interlace	LSC	On/Off
S/N Ratio	>52 dB	Image Conversion	Freeze/V-Flip/H-Flip/Rotate/Nega (On/Off)
White Balance	ATW / AWC / PUSH / Manual Adjustable	Sharpness	Adjustable
Electronic Shutter Control (ESC)	Auto/Manual 1/60 s ~ 1/100,000 s (NTSC) 1/50 s ~ 1/100,000 s (PAL)	3- Axis	Available
Backlight Compensation (BLC)	Low, Middle, High, Off Adjustable	Dimension	144(Ø) x 104(H)mm
OSD	Built in	Video Output	CVBS : 1.0Vp-p / 75Ω
Privacy Masking	On (6 Zones) / Off	Lens	2.8-12mm AVF Lens
Motion Detection	On (240 Zones) / Off	Ingress Protection	IP68
WDR	Off/On Selectable	Power	DC 12V
HLM	Adjustable	Operating Temperature/Humidity	-10° ~ +50° / 30% ~ 80% RH
Adaptive Tone-curve Reproduction (ATR)	-	Storage Temperature/Humidity	-20° ~ +60° / 20% ~ 90% RH
Digital Noise Reduction	3DDNR (Low, Middle, High, Off)		

