

LE5016D-NH

High-Performance, High Resolution Hybrid DVR

Available in 8 or 16 Channels



FEATURES

- 8 or 16 Looping Analog Channels
- Supports up to 2 IP cameras (LG & Axis)
- 704 x 480 (4CIF) Real-Time Recording Resolution
- H.264 Compression for small file sizes
- Up to 8TB Storage Available
- eSATA port for Quick and Easy Archiving
- Bidirectional Audio Support
- ATM/POS Recording & Search
- Email/Client Alarm Notification
- Built-in DVD Burner
- VGA and Main/Spot BNC Monitor Output
- Client Software and Smart Phone App included

SPECIFICATIONS

Video	Input	Analog Camera	16	Storage	Internal HDD	Interface Type	SATA II	
	Output	IP Camera	2		External HDD	Max. Capacity	Up to 4 HDDs	
Audio	Input Output	Loop Through	16	Backup	Supportable Device	Interface Type	e-SATA	
		Composite	1			Max. Capacity	Unlimited	
Alarm	Input Output	VGA	1	Serial I/F	PTZ Control ATM / POS	Max. Capacity	Yes	
		Spot	1				Network	Network Connection
Recording	Frame Rate (/sec)	NTSC	480 fps @ 352x240	Security	User Level Management Data Integrity Check (Watermark)	Yes		
			480 fps @ 704x240				Bandwidth Control	Up to 120 fps
		PAL	480 fps @ 704x480					Yes
			400 fps @ 352x240				5 Levels Continuous / Alarm / Motion / Instant / Panic / Text	
Search	Playback Function Search Mode	NTSC	400 fps @ 704x240	Power Source	AC Free 100-240V, 50/60Hz	0°C ~ 40°C / 0% ~ 80%RH (Non- Condensing)		
			400 fps @ 704x480					
Display	Frame Rate (/sec) Division Mode	PAL	480 fps	Operating Temperature / Humidity	15.10 lbs	16.93 x 16.93 x 3.78 inches		
			400 fps					