

LNB3100

1.3 Megapixel Day/Night IP Indoor Box Security Camera

Up to 720p Full HD Resolution and Features Dynamic Profile Streaming



FEATURES

- 1/3 in progressive scan CMOS image sensor
- High resolution video up to 1280 x 1024 @ 30 fps, 1280 x 720 (720p) @ 30 fps
- H.264/MJPEG dual codec video streaming
- Digital day/night improves the camera's low light sensitivity
- Enhanced imaging with 2D + 3D DNR and WDR
- Sens-up automatically enhances DSS to produce brighter images in low light conditions
- Dynamic profile streaming (3 main streams + 4 regions of interest) brings multi-camera capabilities and custom views to a single camera
- LG Ipsolute mobile app (Android + iPhone) available
- ONVIF and PSIA compliant
- Micro SD card slot for on-board storage

SPECIFICATIONS

Camera	Image Sensor	1/3" CMOS	Network	Protocols	IPv4/6 - TCP/IP, UDP, HTTP, HTTPS, RTP, RTSP, DHCP, ICMP, IPv4 - FTP, SMTP, NTP, ARP, SNMP v1/v2c/v3, DDNS (LG)	
	Scanning Mode	Progressive Scan		Security	Password Protection, HTTPS (SSL, TLS)	
	Resolution	Up to 1280 x 1024		Number of Connections	Up to 10	
	Effective Pixels	Approx. 1.3 Megapixel		General	Power Requirements	PoE / DC12V
	Minimum Illumination	Color: 0.3 Lux @ F1.2 B/W: 0.3 Lux @ F1.2			Power Consumption	5.9 W
	Day/Night	Digital (Auto/Day/Night)			Weight	0.79 lbs
	Wide Dynamic Range	80dB			Dimensions (in.)	2.7 (W) x 2.13 (H) x 4.78 (D)
	Electronic Shutter (sec)	1/30 to 1/10000			Operating Temperature	14°F - 122°F
	Gain Control	Auto			Storage Temperature	-4°F - 140°F
	White Balance Mode	Auto (ATW, AWC Push), Manual			Operating Humidity	0% - 80%RH
Sense-up (DSS)	Yes	Color / Material	Black & Silver / Aluminum			
Noise Reduction	2D+3D DNR	Approvals	UL, FCC, CE, KCC, Gongan			
Lens	Lens Type	CS Mountable	System Requirements		Operating System	Windows XP Professional, Windows VISTA, Windows 7
	Iris	Manual/DC Auto Iris Support		Processor	Intel Core 2 Quad Q6700 (2.66 GHz) or above	
Video	Video Compression Format	H.264 (High Profile Supported), MJPEG		Memory	2 GB or above RAM	
	Codec Streaming Capability	Dynamic Profile Streaming (up to 7)		Web Browser	Microsoft Internet Explorer 7.0 or above	
	Maximum Frame Rate	30 fps @ 1280 x 1024, 30 fps @ 720p		Supplied Accessories	CD ROM (User's Guide, IP Utility, LG Ipsolute VMS Suite)	
	Bit Rate	256 kbps to 10,240 kbps			Installation Manual	
Bit Rate Mode	CBR, VBR					
Features	Motion Detection	Yes				
	Event Notification	Email, FTP				
	Privacy Mask	Yes				
	Interface					
	Ethernet	RJ-45 10/100 BASE-T				
	Analog Video Output	1x RCA Out				
SD Card Slot	1x Micro SD					