



### FEATURES :

- 8 Port 10/100M Nway (Auto-negotiation) Switch
- 8 PSE/PoE function ports
- Supporting the power Max. 15.4 W for each PSE/PoE port
- 11" Desktop size with metal case
- Can be installed in a 19" cabinet by rack-mount kits
- Auto-learn of networking configurations
- Auto-detect full/half-duplex modes for any port
- Dedicated full-duplex 200Mbps bandwidth
- Store-and-Forward switching methods
- IEEE 802.3x flow control for full-duplex and back-pressure flow control for half-duplex
- Non-blocking & Non-head-of-line blocking full wire speed forwarding
- Auto-MDI/MDI-X function for any port / Smart plug & play

### SPECIFICATION :

<b>Standards</b>	IEEE 802.3af / IEEE 802.3 10BaseT / IEEE 802.3u 100BaseTX / IEEE 802.3x Flow control
<b>Filtering/Forwarding Rates</b>	100Mbps port - 148,800pps 10Mbps - 14,880pps"
<b>Transmission Media</b>	10BaseT Cat. 3, 4, 5 UTP/STP 100BaseTX Cat. 5 UTP/STP"
<b>LED Indicators</b>	Per Port: LINK/ACT, PoE ACT/Status Per Unit: Power"
<b>Power Input</b>	100 - 240V/AC, 50 - 60Hz
<b>Power Output</b>	48V/DC Per Port Output -15.4 W Max Per Port 8 Ports at Full 15.4 W Output Supported
<b>Power Consumption</b>	130 Watts (Max)
<b>Dimensions</b>	266 x 160 x 44 mm (L x W x H)
<b>Weight</b>	1.6 kg
<b>Operating Temperature</b>	0 to 55°C
<b>Storage Temperature</b>	-20 to 90°C
<b>Humidity</b>	10 to 90% RH (non-condensing)
<b>Certifications</b>	FCC Class A, CE

### DIMENSIONS : (Unit : mm)

266 x 160 x 44

