

## **6716 Series Hybrid NVR**


16-Channel Recording Platform





The **16-channel Hybrid NVR** from March Networks® delivers video that's always there when you need it, and the advanced tools that allow you to quickly find the evidence you need. Get your job done faster — from installation to investigation — with this appliance-based hybrid NVR as the backbone. This recording platform reinforces our reputation for manufacturing the most robust, reliable, and feature-rich recorder on the market, and allows you to migrate from 100% analog to 100% IP video at your own pace.

From the small, local-control user with just a few cameras, who does not want to connect the recorder to a network...to the largest enterprise user with globally dispersed sites and thousands of recorders... this platform offers a solution that will feel tailor-made to fit each unique application.



## **Key Benefits**

- Meets privacy guidelines. Privacy protection features, such as privacy masking, operator access restrictions, and the ability to delete archived video clips, complies with video surveillance guidelines across Europe and the Middle East.
- ▼ Embedded, Linux-based, and purpose-built. Spend more time performing investigations and less time dealing with maintenance issues that can plague a PC-based recorder.
- All camera licenses included. No need to pay for separate channel licenses; benefit from a full-featured recording platform right out of the box.
- Configurable recording policies. Record video based on user-definable variables like schedule, motion, analytics, etc.
- Real-time health monitoring. Be alerted to camera, recorder and network issues within seconds.
- Network policies for bandwidth protection. Maximize overall system performance with features like bandwidth throttling, maximum retention settings, multi-sector archiving, and selective video recording.
- ▼ Front panel QR code. Use March Networks' free GURU Smartphone App to scan the recorder's QR code to check warranty status, get in-field diagnostics support, do on-site wireless provisioning, or even initiate an express RMA.
- Recorder docking station. Keep all connections clean and securely connected to the back of the unit for quick, easy installation of the recorder, as well as removal for service and maintenance.
- Powerful video management software. With March Networks Command™ Recording Software and Command Enterprise Software, you'll be equipped with the features and tools you need to easily manage your video surveillance system, including innovative search tools, mass management, Windows® Active Directory integration, and health monitoring.

Get rock-solid reliability and best-in-class features in a platform for up to 16 analog or IP cameras—or any combination of both—in a platform that complies with your region's privacy guidelines.

## 6716 Series 16-Channel Hybrid NVR

MODELS				
6716 R series	16 channels, 16 analog inputs, 25fps (PAL) / 30fps (NTSC) throughput, rack mount			
VIDEO				
Analog Capacity	25fps (PAL) / 30fps (NTSC) concurrent at full 4CIF/D1 across 16 channels; 400fps (PAL) / 480fps (NTSC)			
Video Compression	H.264, M-JPEG, CIF/2CIF/4CIF resolution			
Analog Camera Inputs	16 maximum			
IP Camera Inputs	16 maximum			
IP Camera Performance	With all analog cameras enabled, IP cameras are not available With all analog cameras disabled, IP camera capacity = 48 Mbps (3 Mbps / camera)			
Video Output	Composite or HDMI			
AUDIO				
Analog Audio Inputs	4, unbalanced, 10kΩ, 1Vp-p typical			
Analog Audio Outputs	2, unbalanced, 600Ω, IVp-p			
Analog Audio Codec	G.711, 8 bit/8kHz, 64 kBit/s, unidirectional			
NETWORK				
Network 1				
Network 2	GigE port for connection to camera network			
Security	Industry standard TLS 1.2 with strong AES encryption, HTTPS encryption, strong hashing algorithms SHA256, continuous security vulnerability assessment			
Interface	10/100/1000Base-T Ethernet (2 x RJ-45)			
SYSTEMS / NETWORK MANAGEMENT				
Bandwidth Throttle	Yes (can include exceptions on a per-IP address basis)			
Bandwidth Scheduling	· · · · · · · · · · · · · · · · · · ·			
Adaptive Bandwidth	Yes			
Remote Connection	TCP/IP (IPv4)			
Concurrent Remote Connections	No set limit			
Internal Battery	Enables systematic shutdown; no external UPS communication required			
ANALYTICS				
Included	Motion detection			
Optional	Camera obstruction, field-of-view monitoring, trip wire, loitering, presence detection			
STORAGE				
Internal Hard Drives	up to four 3.5" HDDs			
Individual Drive Capacity	3 TB or 4 TB			
Total Storage Capacity	Up to 16 TB			
Drive Type	Serial ATA (SATA)			

ALARM INPUTS/OUTPUTS				
Alarm Inputs	8 current loop inputs, supporting open and closed detection			
Relay Outputs	4 relay switch outputs (30VDC, 1A); programmable event driven			
PHYSICAL				
Dimensions (HxWxD)	8.0 x 44.2 x 40.6 cm / 3.1 x 17.4 x 16.0 in 2U high, 19" rack; wall mount			
Mounting				
Weight	8.4 Kg (18.5 lbs) (with docking station) Add 0.7 Kg (1.5 lbs) per HDD			
ENVIRONMENTAL				
Operating Temperature	5° to 40°C / 41° to 105°F			
Heat Dissipation	Maximum 255 BTU per hour (system plus 4 hard drives)			
Humidity	5% to 95% RH (non-condensing)			
Storage Conditions	-40° to 70°C / -40° to 158°F			
ELECTRICAL				
Internal Power Supply	115/230 VAC (auto-sensing), 2.3A, 50-60Hz			
Power Consumption	75W Max			
REGULATORY				
Safety	IEC60950-1 (ed.2), UL 60950-1 (ed.2), CSA C22.2 No. 60950-1-07 (ed.2)			
EMC	FCC 47 CFR Part 15, Subpart 15, ICES-003, EN55022, CISPR 22, AS/NZS CISPR 22, EN61000-3-2, EN 61000-3-3, EN50130-4, EN55024			
Compliance Marking	CE-mark, cULus, C-tick, WEEE			

ORDERING INFORMATION		
RECORDERS		
30258-106	6716 R NVR, 1 x 3 TB	
30258-107	6716 R NVR, 2 x 3 TB	
30258-108	6716 R NVR, 3 x 3 TB	
30258-109	6716 R NVR, 4 x 3 TB	
30258-113	6716 R NVR, 4 x 4 TB	
ACCESSORIES		
28181	Wall Mount Kit	
36809	Edge 8e HD Encoder	



## 2-year Advance Replacement plan on all NVRs:

Mirroring

- · Options for Repair & Return or Advance Replacement
- March Networks incurs all shipping costs—both ways—for AR's
- All NVR components are covered, including HDDs

North America	. 1800 563 5564
Latin America	+5255 5259 9511
Europe	. +39 0362 17935
Asia	+65 6818 0963
Australia and New Zealand	+61 1300 089 419
Middle Fast and Africa	+971 4 399 5525

