



ΟΠνιειs

## 8732 and 8532 Series Hybrid NVR

MARCH

MARCH

**32-Channel Recording Platform** 



R-series (rack mount)

## The **32-channel Hybrid NVR** from

S-series

(desktop)

March Networks<sup>®</sup> delivers video that's always there when you need it, and the advanced tools that allow you to quickly find the evidence you need. Get your job done faster — from installation to investigation — with this appliancebased hybrid NVR as the backbone. This recording platform reinforces our reputation for manufacturing the most robust, reliable, and feature-rich recorder on the market, and allows you to migrate from 100% analog to 100% IP video at your own pace.

From the small, local-control user with just a few cameras, who does not want to connect the recorder to a network... to the largest enterprise user with globally dispersed sites and thousands of recorders... this platform offers a solution that will feel tailor-made to fit each unique application.

## **Key Benefits**

()

()

- **Embedded, Linux-based, and purpose-built.** Spend more time performing investigations and less time dealing with maintenance issues that can plague a PC-based recorder.
- All camera licenses included. No need to pay for separate channel licenses; benefit from a full-featured recording platform right out of the box.
- Configurable recording policies. Record video based on user-definable variables like schedule, motion, analytics, etc.
- Real-time health monitoring. Be alerted to camera, recorder and network issues within seconds.
- Network policies for bandwidth protection. Maximize overall system performance with features like bandwidth throttling, maximum retention settings, multi-sector archiving, and selective video recording.
- Front panel QR code. Use March Networks' free GURU Smartphone App to scan the recorder's QR code to check warranty status, get in-field diagnostics support, do on-site wireless provisioning, or even initiate an express RMA.
- Recorder docking station. Keep all connections clean and securely connected to the back of the unit for quick, easy installation of the recorder, as well as removal for service and maintenance.
- ▼ Powerful video management software. With March Networks Command<sup>™</sup> Recording Software and Command Enterprise Software, you'll be equipped with the features and tools you need to easily manage your video surveillance system.
- ✓ Get a complete view of your business. Supplement your surveillance video with March Networks Searchlight<sup>™</sup> Software and the Brickstream<sup>®</sup> Analytics Sensor. This further enhances your evidence by incorporating powerful business analytics (e.g., people counting, queue length, and wait times), and ancillary data (e.g., POS, ATM, teller, RFID, weapon detection, and license plate recognition).

Get rock-solid reliability and best-in-class features in a platform for up to 16 analog and 16 IP cameras, or a 32-channel all IP installation.



## 8732 and 8532 Series Hybrid NVR

MODELS		ALARM INPUTS/OUTPUTS				
8732 R series	32 channels, 30fps, rack mount				in and closed detection	
8532 R series	32 channels, 15fps, rack mount	Alarm Inputs Relay Outputs		8 current loop inputs, supporting open and closed detection		
8532 S series	32 channels, 15fps, desktop			4 relay switch outputs (30VDC, 1A); programmable event driven		
VIDEO		PHYSIC	· A I	unven		
Channel Capacity	8732 R 30fps concurrent at full 4CIF/2CIF/CIF across		ons (HxWxD)			
channel capacity	32 channels (480fps)	R series S series Mounting: R series S series		3.1 x 17.4 x 16.0 in (8.0 x 44.2 x 40.6 cm) 3.2 x 16.9 x 16.0 in (8.1 x 43.0 x 40.6 cm) 2U high, 19" rack, wall mount, desktop Wall mount, desktop		
	8532 R 15fps concurrent at full 4CIF/2CIF/CIF across 32 channels (240fps) 8532 S 15fps concurrent at full 4CIF/2CIF/CIF across					
Video Compression	32 channels (240fps) H.264. CIF/2CIF/4CIF resolution	<b>S series</b> 13 lbs (5.9		18.5 lbs (8.4 Kg) (with docking station)		
Max Analog/IP Camera Inputs	16/32				bs (5.9 Kg) (no docking station) d 1.5 lbs (0.7 Kg) per HDD	
IP Camera Performance	With all analog cameras enabled,	ENVIRONMENTAL				
	IP camera capacity = 48 Mbps	<b>Operating Temperature</b> 5°C to 40°C (41°F to 105°F)				
	With all analog cameras disabled,	Heat Dissipation Humidity		Maximum 255 BTU per hour (system plus 4 hard drives)		
	IP camera capacity = 96 Mbps			5% to 95% RH (non-condensing)		
Video Output	Composite or HDMI	Storage C	Conditions	-40°C to 70°C (-40°F to 158°F)		
AUDIO		ELECTR	RICAL			
Analog Audio Inputs	4, unbalanced, 10k $\Omega$ , 1Vp-p typical	Internal P	ower Supply	115/230 VAC (auto-sensing), 2.3A, 50-60Hz		
Analog Audio Outputs	2, unbalanced, 600Ω, 1Vp-p	Power Co	onsumption	75W Max		
Analog Audio Codec	G.711, 8 bit/8kHz, 64 kBit/s, unidirectional	REGUL	ATORY			
NETWORK		Safety		IEC60950-1 (ed.2)		),
Network 1	GigE port for connection to corporate network	CSA C22.2 No. 60950-1-07 (ed.2) EMC FCC 47 CFR Part 15, Subpart 15, ICES-003, EN55022,		003 EN55022		
Network 2	GigE port for connection to camera network	CISPR 22, AS/NZS CISPR 22,EN6100				
Security	Industry standard TLS 1.2 with strong AES encryption, HTTPS encryption, strong hashing algorithms SHA256, continuous security vulnerability assessment	Compliance Marking		EN50130-4,EN55024 CE-mark, cULus, C-tick, WEEE		
Interface	10/100/1000Base-T Ethernet (2 x RJ-45)					
SYSTEMS / NETWO	PRK MANAGEMENT					
Bandwidth Throttle	Yes (can include exceptions on a per-IP address basis)					
Bandwidth Scheduling	Yes	Pa	ower Audio	Audio	Video	Alarm
Adaptive Bandwidth	Yes	Connector In		Out	Inputs	Inputs
Remote Connection	TCP/IP (IPv4)				2 - 1 - 1 - 10 - 11	
Concurrent Remote Connections	No set limit					
Internal Battery	Enables systematic shutdown; no external UPS communication required	130.30				
ANALYTICS			12 Volt	2 US		
Included	Motion detection	r	Out	RS-232 Port.	LE	Ds Output
Optional	Camera obstruction, field-of-view monitoring, trip wire, loitering, presence detection	Fuse RS-485 HD Monitor Relay Compartment Output Outputs				
STORAGE						
Internal Hard Drives	1-4 3.5" HDDs					
Individual Drive Capacity	Up to 12 TB		3-year warr	anty on all recorders:		
Total Storage Capacity	Up to 48 TB	<ul> <li>Options for Repair &amp; Return or Advance Replacement</li> <li>March Networks incurs all shipping costs—both ways—for AR's</li> <li>All recorder components are covered, including HDDs</li> </ul>				
Drive Type	Serial ATA (SATA)					
Mirroring	Yes					

North America 1800 563 5564
Latin America +5255 5259 9511
Europe+39 0362 17935
Asia+65 6818 0963
Australia and New Zealand+61 1300 089 419
Middle East and Africa+971 4 399 5525

© 2019 March Networks. All rights reserved. Information in this document is subject to change without notice. MARCH NETWORKS, March Networks Command, March Networks Searchlight, March Networks RideSafe, and the MARCH NETWORKS logo are trademarks of March Networks Corporation. All other trademarks are the property of their respective owners. 060-3159-00-1 marchnetworks.com

