



Specification

Item	NVS121A
Remote management	Configuration and system log can be accessed via web browser and Ftp application remotely
Networking	
Protocol	TCP, UDP, IP, HTTP, DHCP, PPPoE, RTP, RTSP
Ethernet	Ethernet (10/100Base-T), RJ-45 connector
Video	
Compression	MPEG-4 / MJPEG Selectable
Video input	1 BNC composite video input with NTSC / PAL auto sensing
Analog output (loop-through)	1 Vp-p composite output 75ohm.
Image size	Full D1 (720X480 in NTSC, 720X576 in PAL)
	CIF (350X240 in NTSC, 352X288 in PAL)
	QCIF (160X112 in NTSC, 176X144 in PAL)
Image quality	CIF/ Full D1/ QCIF
Others	Watch dog timer 5 sec.
	2 DI/ 2 DO event triggered via Ethernet
	Layer 2, 3
Audio	Yes
Frame rate	30fps at 720X480 - NTSC
	25fps at 720X576 - PAL
RS485	1 x RJ-45
Viewing system requirement	
Protocol	Standard internet TCP/IP
Operating system	Win 2000, Win XP
Browser	Internet Explorer 6.0 or above
Security	User authorization needed for protecting camera access
Pan/tilt/zoom control	Automatic PTZ camera detection with Pelco-D protocol
	Clear data command driver is supported
LED indicator	Heartbeat, status, network
General	
Power input	DC12V
Operating temperature	0°C ~ 50°C (40 ~122°F)
Operating humidity	10% ~ 90%
Dimensions (W x H x D)	112 x 37.2 x 119 mm
Weight	350g (0.6 lb.)