



SDM126 Indoor Mini Dome Camera

600TVL, F2.0, f:2.8 mm, Digital Day/Night, DC12V



Specification

Signal System	NTSC		PAL	
Image System				
Image Area	4.9mm x 3.7mm			
Image Sensor	Sony 1/3" Super HAD CCD II			
Effective Pixel (H x V)	768 x 494		752 x 582	
Electronic				
Scanning System	2:1 Interlace V: 59.94Hz, H: 15.734KHz		2:1 Interlace V: 50Hz, H: 15.625KHz	
Sync System	Internal			
Horizontal Resolution	600 TVLines			
Built-in Lens	F2.0, f=2.8mm			
View Angle	f=2.8mm Horizontal:90°/ Vertical: 80°			
Gamma Correction	0.45			
Min. Illumination	0.2 Lux (F2.0@30IRE)			
S/N Ratio	More than 50dB (AGC off)			
White Balance	Auto			
Electronic Shutter	1/60 ~ 1/100,000 Sec.		1/50 ~ 1/100,000 Sec.	
BLC	Off			
Day/Night Mode	Auto			
Gain Control	Auto			
Video Output	1Vpp composite output 75 ohm			
Power supply				
Power Requirement	DC12V ± 10%			
Power Consumption	1.5 W(max)			
Environment				
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)			
Operating Humidity	90% RH			
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)			
Mechanism				
Dimensions (D X H)	Ø107mm x 64 mm			
Weight (g)	300 g			