





Model	MS-C5362-FPB
Mega Piksel	5.0 Mega Piksel
Görüntü Sensörü	1/2.9" Progressive Scan CMOS
Maksimum Çözünürlük	2560 x 1920
Video Sıkıştırma	H.265+ / H.265(HEVC) / H.264+ / H.264 / MJPEG
Frame Hızı	20 Fps&2560X1920 / 20 Fps&2592x1520 / 30 Fps&2304x1296 / 30 Fps&1920x1080 30 Fps&1280x960 / 30 Fps&1280x720 / 30 Fps&704x576
Lens	2,8-12 mm Motorize Lens @ F1.4 / P-iris (Opsiyonel)
Görüş Açısı	H67.2°~H30.3°/D83.4°~D36.6°/V51.4°~V24°(2.8~12mm)
IR Led Sayısı	4 Array Led
Gece Görüş Mesafesi	60-100 mt.
Minimum Işık Oranı	Color: 0,005 Lux@F1.2 / B&W: 0 Lux (IR Led Açık)
Day&Night	True Day&Night (ICR)
Wide Dyn. Range (WDR)	Super WDR up to 120 dB
Digital Noise Red. (DNR)	3D-DNR
ROI / BLC	Var
Ses Sıkıştırma	G.711/AAC
Maskeleme	Var
Hareket Algılama	Var
SIP/VoIP Desteği	Var, Voice & Video-over-IP
Olay Tetiklemeler	Hareket Algılama, Network Kaybı
Shutter Hızı	1/5 ~ 1/100.000 sn.
Video Bit Rate	16 Kbps ~ 16 Mbps (CBR/VBR)
Ethernet Girişi	1 Adet RJ 45 10/100M
Network Depolama	NAS (NFS, SMB/CIFS Destekler)
SD Card Desteği	Var (128 GB)
Power Over Ethernet (PoE)	Var
Onvif	Profile S
Protokoller	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, SIP, Ipv6 PPPoE, VLAN
Audio I/O	1/1
Alarm I/O	1/1
Koruma Sınıfı	IP 67
Çalışma Voltajı	DC 12V

5.0 Mp Pro IR Bullet IP Kameralar


Day




Night




WDR: On



WDR: Off




ROI: Off




Region of interest

ROI: On





Lower Quality
Higher Quality


Mask: Off





Mask: On



































"Türkiye'nin Güvenlik Çözümü"