





Model	MS-C8262-FPB
Mega Piksel	8.0 Mega Piksel <b>4K Pro Bullet</b>
Görüntü Sensörü	1/2.5" Progressive Scan CMOS
Maksimum Çözünürlük	3840 x 2160
Video Sıkıştırma	<b>H.265+ / H.265(HEVC) / H.264+ / H.264 / MJPEG</b>
Frame Hızı	30fps(3840×2160), 30fps(3072×2048), 30fps(2560×1920), 30fps(2592×1520), 30fps(2048×1536), 30fps(1920×1080), 30fps(1280×960), 30fps(1280×720), 30fps(704×576)
Lens	4-12 mm Motorize Lens @ F1.4 / P-iris (Opsiyonel)
Görüş Açısı	H81.6°~H38.2°/D92.8°~D43.8°/V46.8°~V21.6°(4~12mm)
IR Led Sayısı	4 Array Led
Gece Görüş Mesafesi	60 mt.
Minimum Işık Oranı	Color: 0,006 Lux@F1.2 / B&W: 0 Lux (IR Led Açık)
Day&Night	True Day&Night (ICR)
Wide Dyn. Range (WDR)	<b>Super WDR up to 120 dB</b>
Digital Noise Red. (DNR)	3D-DNR
ROI / BLC	Var
Ses Sıkıştırma	G.711/AAC
Maskeleme	Var
Hareket Algılama	Var
SIP/VoIP Desteği	Var, Voice & Video-over-IP
Olay Tetiklemeler	Hareket Algılama, Network Kaybı
Shutter Hızı	1/5 ~ 1/100.000 sn.
Video Bit Rate	16 Kbps ~ 16 Mbps (CBR/VBR)
Ethernet Girişi	1 Adet RJ 45 10/100M
Network Depolama	NAS (NFS, SMB/CIFS Destekler)
SD Card Desteği	Var (128 GB)
Power Over Ethernet (PoE)	Var
Onvif	Profile S
Protokoller	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, SIP, Ipv6 PPPoE, VLAN
Audio I/O	1/1
Alarm I/O	1/1
Koruma Sınıfı	IP 67
Çalışma Voltajı	DC 12V

## 8.0 Mp Pro IR Bullet IP Kameralar


Day




Night




WDR: On



WDR: Off




ROI: Off



Region of interest


ROI: On




Lower Quality


Higher Quality


Mask: Off





Mask: On



































"Türkiye'nin Güvenlik Çözümü"