

Mini IP Bullet Camera
ONL-51IR

OINONE
your cctv choice



| Hardware | |
|------------------------------|---|
| Sensor | 1/3" Progressive Scan CMOS 1.3 MP |
| Effective Pixels | 1280(H)×960(V) |
| Min.Illumination | 0.01Lux/F1.2(COLOR), 0.001Lux/F1.2(B/W), 0Lux(IR On) |
| Day/Night | Auto,dual IR-Cut filter, DWDR |
| IR LED | 36PCS Φ5 IR LED IR 30M |
| Max S/N Ratio | 39dB |
| Electronic Shutter | Rolling Shutter |
| Lens | 3.6mm Lens |
| Network Interface | 10/100M BASE-TX,RJ-45 connector |
| RS485 | Default as RS485 port for PTZ, 1ch Alarm input or 1ch alarm output optional |
| Audio video encoding | |
| Video Compression | H.264 Main Profile; |
| Resolution | HD 960P (1280*960) 1-25fps |
| Sub Stream | CIF(352*288)/QVGA(320*240)/QCIF(176*144) 1-30fps |
| Video Bitrate | 32Kbps~4Mbps,Supports CBR/VBR |
| Privacy Mask | 4 configurable regions |
| Auto Image Control | Auto Exposure Control (AEC); Auto White Balance (AWB); Auto Band Filter (ABF) |
| Functions | Auto Black Level Calibration (ABLC) |
| Image Controls | Color saturation, hue, gamma, sharpness , lens correction, defective pixel canceling, and noise canceling |
| Data trans. & Storage | |
| Data storage | Video and Image |
| Recording | Recording set up to record by motion trigger,alarm trigger, manual, or schedule |
| Alarm Output | FTP,E-mail, Explorer, Software |
| Network protocol | TCP/IP、 UDP、 RTP、 RTSP、 RTCP、 HTTP、 DNS、 DDNS、 DHCP、 FTP、 NTP、 PPPOE、 SMTP、 UPNP |
| ONVIF protocols | Support 1.02 version |
| Remote View | IE 6.0 or later, max 10 users |
| General Parameters | |
| Environmental Casing | Waterproof (IP66 Rated), Outdoor Use |
| Operating Temperature | -20 °C ~ 50 °C (-4 °F ~ 122 °F) for DC 12V |
| Operating Humidity | 0% -85% RH |
| Power | PoE, DC12V 2.0A |
| Power Consumption | 9 W(MAX) |
| Dimension | 179mmx67mmx67mm |
| Weight | 390g |
| Material | Metal |

Dimensions

