

# PXD-DN5601

## Internal Dome Camera



### Camera Specification

CAMERA	NTSC	PAL
Imaging Sensor	1/3" SONY Super HAD CCD II	
Signal System	NTSC : 525 Lines	PAL : 625 Lines
Scanning System	2:1 Interlace	
Scanning Frequency	H:15.734 kHz / V:59.94 Hz	H:15.625 kHz / V:50 Hz
S/N Ratio	More than 52dB (AGC Off)	
Horizontal Resolution	Horizontal : 560 TV-Line (Color) / 660 TV-Line (B/W)	
Video Output Level	1.0 Vp-p (75Ω, Composite)	
Min. Illumination	Color : 0.05Lux(50IRE@F1.2)	
Sync System	Internal / Line Lock	
O.S.D	Built-in & Available	
Electronic Shutter Speed	Auto / Flicker	
	1/60sec ~ 1/100,000sec	1/50sec ~ 1/100,000sec
White Balance	AWB / AWC-SET / MANUAL / INDOOR / OUTDOOR / ATW	
Backlight Compensation	BLC / Off	
D - WDR	-	
Gain Control	Low / Middle / High / Off	
Adjust	CONTRAST / SHARPNESS / CB_GAIN / CR_GAIN (Level Adjustable)	
Language	Multi Language(Selectable)	
Camera Title	On / Off (Selectable)	
Day & Night	Auto / B.W / Color (Selectable)	
Digital Zoom	-	
Privacy Masking	-	
Motion Detection	On / Off (4 Zone Selectable)	
DNR (Digital Noise Reduction)	-	
Sens - up (Frame Integration)	-	
D - EFFECT	-	
DPC	-	

### Camera Feature

- 1/3" Sony Super HAD II CCD Sensor
- DSP
- 560TVL High Resolution
- High Sensitivity : 0.1Lux
- Motion Detection : 4 Area

### Structure Feature

- 3.6mm Fixed Iris Lens(F = 1.4)
- OSD Control Board with 2nd Video Out Put
- Wall Mount Bracket Support
- Voltage 12VDC

### Structure Specification

MECHANICAL	
Dimension	112(D) X 112(W) X 87(H)
Weight	0.4kg
ENVIROMENTAL	
Construction	Plastic
Ingress Protection	-
Operating Temp	-10°C ~ 50°C
Storage Temp	-10°C ~ 50°C
Humidity	0% to 90%
ELECTRONICAL(Power Consumption)	
Supplied Voltage	DC12 ± 10% or AC24 ± 10%
Camera	120mA
CERTIFICATION	
CE, FCC, RoHS, KCE	Yes

### Dimension

