

SRD-1676D

16CH 1280H Real-time Coaxial DVR





Key Features

- 16CH 1280H real-time DVR
- Up to 480(NTSC) / 400(PAL)fps recording rate
- HDMI / VGA video output
- 16CH audio inputs / 1CH audio output
- Max. 4 internal HDDs
- PTZ control via coaxial cable (Samsung CCVC, Pelco-C)
- DVD-RW, Smart phone support (Android / iOS)
- Accurate still image (De-Interlace support each channel)
- Enhanced Network Bandwidth up to 32Mbps

Dimensions

Unit : mm (inch)



| | | SRD-1676D |
|--------------------|-----------------------------|--|
| DISPLAY | | |
| Video | Inputs | 16 Composite video 0.5-1 Vpp, 75 ohm automatic termination |
| | Resolution | NTSC : 1280 x 480, 720 x 480 / PAL : 1280 x 576, 720 x 576 |
| Live | Frame Rate | NTSC : 480fps / PAL : 400fps |
| | Resolution | NTSC : 1280 x 480, 720 x 480 / PAL : 1280 x 576, 720 x 576 |
| | Multi Screen Display | 1 / 4 / 7 / 9 / 13 / 16 / 16A / Sequence / PIP |
| PERFORMANCE | | |
| Operating System | Embedded | Linux |
| | Compression | H.264 |
| Recording | Record Rate | NTSC : Up to 480fps@1280 x 480 / PAL : Up to 400fps@1280 x 576 NTSC : Up to 480fps@704 x 480 / PAL : Up to 400fps@704 x 576 NTSC : Up to 480fps@704 x 240 / PAL : Up to 400fps@704 x 288 NTSC : Up to 480fps@352 x 240 / PAL : Up to 400fps@352 x 288 |
| | Mode | NTSC : Manual, Schedule (Continuous / Event), Event (Pre / Post), Time lapse (1 ~ 30 fps) PAL : Manual, Schedule (Continuous / Event), Event (Pre / Post), Time lapse (1 ~ 25fps) |
| | Event | Video loss, Motion (Level 1 ~ 10), Alarm, Tampering (Level 1 ~ 3) |
| | Overwrite Modes | Selectable (Stop / Continuous) |
| | Pre-alarm | Up to 30sec (5, 10, 20, 30sec) |
| | Post-alarm | Up to 6hour (5, 10, 20, 30sec, 1, 3, 5, 10, 20min, 1, 2, 3, 4, 5, 6hour) |
| Search & Playback | Search Mode | Date/Time, Event, Back up, POS, Motion (*All search include preview function) |
| | Playback Function | Fast forward / backward (2x, 4x, 8x, 16x, 32x, 64x) *Backward play with i-frame only Slow forward / backward (1/2x, 1/4x, 1/8x) Step forward / backward *Backward play with i-frame only |
| Network (IPv4) | Transmission Speed | 4CIF / 2CIF / CIF (NTSC : 120 / 240 / 480fps, PAL : 100 / 200 / 400fps) |
| | Bandwidth | Up to 32Mbps |
| | Bandwidth Control | Selectable |
| | Stream | H.264 (4CIF / 2CIF / CIF selectable) |
| | Max. Remote Users | Search 3 / Live unicast 10 / Live multicast 20 |
| Smart Phone | Protocol Support | TCP/IP, DHCP, PPPoE, SMTP, NTP, HTTP, HTTPS, DDNS, RTP, RTSP, SNMP |
| | Monitoring | SmartViewer, Webviewer, SSM (CMS) |
| | Platform | Android, iOS |
| Storage | Internal HDD | RTP, RTSP, HTTP, CGI |
| | External (e-SATA Interface) | Live 2, Search 1 |
| Security | DVD Writer (Back up) | Up to 4 SATA HDDs |
| | USB (Back up) | 2 External SATA ports (*Expansion bay, Model : SVS-5R/5E) |
| | File Format (Back up) | Yes |
| | Password Protection | 2 USB ports |
| INTERFACE | Data Authentication | BU (DVR player), EXE (Include player), AVI |
| | Watermark | 1 Admin, 10 Group, 10 User per 1 group |
| Monitors | VGA | Watermark |
| | HDMI | 1 VGA (1280 x 720, 1280 x 1024, 1920 x 1080) |
| | Digital spot (2CH) | 1 HDMI (1280 x 720, 1280 x 1024, 1920 x 1080) |
| | Loop Outputs | Digital spot (2CH) *Included OSD on screen, multi mode support (1CH) |
| Audio | Inputs / Output | 16CH |
| | Compression | 16CH line in (Built-in 4CH, option : audio extension cable) / 1CH line out |
| | Sampling Rate | G.711 |
| Alarm | Inputs / Output | 8KHz |
| | Remote Notification | Terminal 16 inputs (NO/NC) / Terminal 4 relay outputs (NO/NC), Rating : 30V DC / 2A, 250V AC / 0.25A |
| Connections | Ethernet | Notification via e-mail |
| | Serial Interface | 1 RJ-45 10/100/1000 Base-T |
| | USB | RS-232/RS-485 (Full duplex) for PTZ, Samsung system keyboard |
| | eSATA | USB 2.0, 2 ports |
| | Application Support | 2 External SATA ports |
| GENERAL | RS-485 Protocol | Mouse, Remote controller |
| | Coax Protocol | Samsung T/E, Pelco-D/P, Panasonic, Phillips, AD, DIAMOND, ERNA, KALATEL, VCL TP, VICON, ELMO, GE |
| | Coax Protocol | Samsung CCVC, Pelco-C |
| Electrical | Input Voltage / Current | 100 ~ 240V AC ±10%, 50/60Hz, Auto ranging |
| | Power Consumption | Max. 60W (With 1x HDD) |
| Environmental | Operating Temperature | +0°C ~ +40°C (+32°F ~ +104°F) |
| | Operating Humidity | 20% ~ 85% RH |
| Mechanical | Dimensions (WxHxD) | 440.0 x 88.0 x 384.8mm (17.32" x 3.46" x 15.15") |
| | Weight (With hard disks) | Approx. 6.6Kg (14.61 lb) |
| Language | Rack Mountable | Yes |
| | Language | English, French, German, Spanish, Italian, Russian, Polish, Czech, Turkish, Netherlands, Portuguese, Swedish, Danish, Rumania, Serbia, Croatia, Hungary, Greek, Finnish, Norwegian, Korean, Japanese, Chinese (Traditional), Thai, Taiwanese (25 Language) |

* The latest product information / specification can be found at www.samsungsecurity.com