

SC-2109-N NVR



Key Features

Original

- SDA+ over LAN technology inside, One-click Access third-party ONVIF camera
- All channel real-time synchronous playback
- Support IE, Chrome, Firefox, Safari, and browser plug-in free
- All channel synchronous live view and playback by smart phone

HD Input & Output

- H.265 / H.264 video formats
- Up to 9 8MP IP camera can be accessed
- HDMI at up to 4K, VGA at up to 1080P

HD Storage & Communication

- 1 HDD supported, Up to 8TB for each
- 1 self-adaptive 10/100M RJ45 interface

Special

- Instant playback for assigned channel during multi-channel live view mode
- Smart search for selected area in the video, and smart playback to improve the efficiency

Specifications

| | | | |
|-----------------------------|--|------------------|--|
| Model | | SC-2109-N | |
| Video / Audio input | IP video input | | 9 Ch. |
| | | | Up to 8 MP |
| | IP audio input | | 9 Ch. |
| | Two-way audio | | 1x RCA (2.0 Vp-p, 1 kΩ) |
| Network | Incoming | Standard | ONVIF, RTSP, HB-protocol |
| | | Bandwidth | 80Mbps |
| | Outgoing | Standard | CGI, RTSP, RTMP(Only for H.264), HB-SDK |
| | | Bandwidth | 80Mbps |
| Video / Audio output | Recording resolution | | Up to 8 MP |
| | HDMI output | | 4K (3840 x 2160)/60Hz, 1080p (1920 x 1080)/60Hz, 720p (1280 x 720)/60Hz, UXGA (1600 x 1200)/60Hz, 1280 x 1024/60Hz |
| | VGA output | | 1080p (1920 x 1080)/60Hz, 720p (1280 x 720)/60Hz, UXGA (1600 x 1200)/60Hz, 1280 x 1024/60Hz |
| | Audio output | | 1x RCA (Linear, 1 kΩ) |
| Decoding | Decoding standard | | H.265 / H.264 |
| | Live view / playback resolution | | Up to 8 MP |
| | Synchronous playback | | All Ch. Synchronous playback |
| HDD | SATA | | 1 SATA interface for 1 HDD |
| | Capacity | | Up to 8TB capacity for each HDD |
| External interface | Network | | 1 10/100Mbps self-adaptive RJ45 interface |
| | USB | | Rear panel: 1x USB3.0 / 1x USB2.0 |
| | Alarm | | 2 in / 1 out |
| | RS-485 | | N/A |
| General | Power supply | | 12V 24W |
| | Operating condition | | -Temperature: -10°C – 55°C (-14°F – 131°F) Humidity: 10 - 90% |
| | Dimensions (WxDxH) | | 254 x 180 x 49.5mm (10" x 7" x 1.9") |