

DS-2AF1-513/515/517-B


WDR Analog High Speed Dome



Key features

- 1/4" Sony EXVIEW HAD progressive scan CCD
- 128x wide dynamic range
- 540 TVL high resolution
- True Day/night
- 3D intelligent positioning function
- 3D digital noise reduction
- IP66 rating

Dimensions



Accessories



	DS-2AF1-513-B (outdoor) DS-2AF1-503-B (indoor)	DS-2AF1-515-B (outdoor) DS-2AF1-505-B (indoor)	DS-2AF1-517-B (outdoor) DS-2AF1-507-B (indoor)
Camera			
Image sensor	1 / 4" SONY EXVIEW HAD progressive scan CCD		
Effective pixel	PAL:752(H)×582(V), NTSC:768(H)×494(V)		
Horizontal resolution	Color: 540 TVL, B / W: 570 TVL		
Signal system	PAL / NTSC		
Min.illumination	Color: 0.7Lux / F1.4 B / W: 0.01Lux / F1.4	Color: 0.65 lux@F1.35 B / W: 0.005 lux@F1.35	Color: 1.4 lux@F1.6 B / W: 0.01 lux@F1.6
White balance	Auto / Manual / ATW / Indoor / Outdoor / Outdoor Auto / sodium lamp		
AGC	Auto / manual		
S / N ratio	≥ 50dB		
DNR	High / Medium / Low / off		
BLC	On / off		
WDR	128x (on / off / auto)		
Anti-shake	--	On / off	
Shutter time	PAL: 1 / 3 ~ 1 / 10,000s, NTSC: 1 / 4 ~ 1 / 10,000s		
Day & night	IR cut filter		
Digital zoom	12x		
Privacy mask	24 privacy masks programmable; a maximum of 8 zones can be masked simultaneously on the same video screen		
Focus model	Auto / semi-automatic / manual		
Lens			
Focal length	4.1-73.8mm, 18X	3.5-98mm,28X	3.4-122.4mm,36X
Zoom speed	Approx.2.0s(Optical Wide-Tele)	Approx.1.7s(Optical Wide-Tele)	Approx.2.7s(Optical Wide-Tele)
Angle of view	48-2.8° (Wide-Tele)	55.8-2.1° (Wide-Tele)	57.8-1.7° (Wide-Tele)
Min. working distance	290-800mm (Wide-Tele)	10-1,500mm(Wide-Tele)	320-1,500mm(Wide-Tele)
Aperture range	F1.4 - F3.0	F1.35 - F3.7	F1.6 - F4.5
Pan and tilt			
Pan Range	360°endless		
Pan Speed	Pan Manual Speed: 0.1° -300° / s, Pan Preset Speed: 540° / s		
Tilt Range	-5°-185°(Auto Mirror)		
Tilt Speed	Tilt Manual Speed: 0.1°-240° / s, Tilt Preset Speed: 400° / s		
Proportional Zoom	Rotation speed can be adjusted automatically according to zoom multiples		
Number of Preset	256		
Patrol	8 patrols, up to 32 presets per patrol		
Pattern	4 patterns, with the total recording time not less than 10 min		
Power-off Memory	Support		
Park Action	Preset / Patrol / Pattern / Pan scan / Tilt scan / Random scan / Frame scan / Panorama scan		
PTZ Position Display	On / Off		
Freeze Frame	Support		
Password Protection	Support		
Zone Scanning / Display	Scanning within programmed zone, display zone title		
Camera Title	Programmable title display		
Compass	Support , the north can be set		
Scheduled Task	Preset / Patrol / Pattern / Pan scan / Tilt scan / Random scan / Frame scan / Panorama scan		
RS-485 communication diagnosis	Including failure information, e.g., wrong address, baud rate errors, et., displayed on the video screen in text		
Manchester code communication diagnosis	Including failure information, e.g., wrong address, baud rate errors s displayed on the video screen in special characters		
Alarm			
Alarm input	2 (7 alarm inputs optional)		
Alarm output	2 relay outputs, alarm response actions configurable		
Alarm action	Preset / Patrol / Pattern / Pan scan / Tilt scan / Random scan / Frame scan / Panorama scan / Relay output		
Input/output			
Monitor output	1.0V[p-p] / 75Ω, NTSC (or PAL) composite, BNC		
General			
Menu language	English, Chinese		
RS-485 protocols	HIKVISION, Pelco-P, Pelco-D, self-adaptive		
Power supply	24 VAC (12 VDC optional)		
Power consumption	Outdoor dome: Max.45 W ; Indoor / In-ceiling dome: Max.20 W		
Working temperature / humidity	-30°C ~ 65°C (-22°F ~ 149°F) (outdoor) / -10°C ~ 50°C (14°F ~ 122°F) (indoor), 90% or less		
Protection level	IP66 standard (outdoor dome), TVS 4,000V lightning protection, surge protection and voltage transient protection		
Mounting	Various mounting modes optional		
Dimensions	Φ 220 × 325.5mm (Φ 8.66" × 12.81") (outdoor), Φ 183.4 × 247mm (Φ 7.22" × 9.72") (indoor)		
Weight (approx.)	5kg (11.02lbs)		