

H.265 320CH 24HDD HOT SWAP NVR  
Model TC-R324320 Spec: E/B/N



#### Features

- Recording resolution 12MP/4K/6MP/5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF IP Camera Input
- Up to 12MP Resolution Recording
- Bandwidth in/out 1280Mbps/640Mbps
- JBOD,RAID0,RAID1,RAID5,RAID6,RAID10, RAID50, RAID60 (>0°C, Each Raid Group Supports up to 100Mbps Input)
- HDD Quota and Group Management
- 4X 100/1000Mbps Self-adaptive Ethernet Interfaces,4 1000Mbps optical port
- Support 320-ch Intelligent Analysis Process
- Smart Search&Recording, Plug&Play
- Support ANR **Function**
- Support N+M Hot Standby Function
- 2x HDMI, 1x VGA, **Different** Video Source, Max Resolution 4K
- 24 SATA, Alarm I/O 8 plus36 switch value /4 plus 18 switch value, Audio I/O 1/1, 4x USB,10x RS-485, 1x RS-232
- 1+1 redundant power
- CE, FCC

#### Dimensions

#### Specification

Video/Audio Input	
Video Input	320-ch
Audio Input	1-ch, 3.5mm
Network	
Incoming Bandwidth	1280Mbps
Outgoing Bandwidth	640Mbps
Mobile Software	P2P&DDNS for IOS&Android
Internet Protocol	TCP/UDP/HTTP/MULTICAST/UPnP/DHCP/PPPoE/DDNS/NFS/FTP/INTP/HTTPS/RTSP/SMTP/HTTPS/SADP/SNMP
Email	Activated by Alarm
ANR	Y, Auto download video from camera SD card, Which was stored when disconnection (Only Support Tiandy ANR IP Camera)
Advanced	Remaining Bandwidth Display, Flow Monitor, Capture Package
Video/Audio Output	
HDMI Output	2-ch Resolution: 4096*2160, 3840*2160, 2560*1600, 1600*1200, 3840*2160, 2560*1600, 2560*1440, 1920*1080, 1280*720, 800*600, 1024*768, 1366*768, 1440*900, 1280*800, 1280*1024, Output mode, Self-adaptive Resolution
VGA Output	Adjustable
I-Frame Record	Y, Only Record Key Frame to Lower Frame Rate
Recording Resolution	12MP/4K(3840*2160,3264*2448,3296*2472)/6MP(2752*2208,3008*2008,2408*2008)/5MP(2560*1920,2592*1944,2592*1920,2528*2128)/4MP(2560*1440,2592*1520)/3MP(2048*1536)/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Audio Output	1-ch 3.5mm
Synchronous Playback	16-ch 4CIF/16-ch 720P/16-ch 1080P/5-ch 4K
Decoding	
Live View/Playback	12MP/4K/6MP/5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Capability	5-ch 4K/20-ch 1080P/40-ch 720P/80-ch 4CIF
Display Split	1/3/4/6/8/9/10/13/16/20/25/32/36/40/64
E-Zoom	Y
Hard Disk	
SATA	24 SATA for 24 HDDs (Hot Swap)
eSATA	Y, Only for Backup
Capacity	Up to 10TB Capacity for Each HDD
NTFS Files System	Y
HDD Management	Group and Quota, Customized Recording Days
RAID	
RAID Mode	JBOD,RAID0,RAID1,RAID5,RAID6,RAID10, RAID50, RAID60 (>0°C, Each Raid Group Supports up to 100Mbps Input)
Hot Backup Disk	Overall and Raid Hot Backup Disk
RAID Management	One-key Configuration, and Support Manual and Auto Rebuild
Redundant Recording	Y, Support 200Mbps Input
External Interface	
Network Interface	4 100/1000Mbps Self-adaptive Ethernet Interfaces,4 1000Mbps optical port
Serial Interface	10 x RS-485, 1 x RS-232
USB Interface	2x USB3.0, 2x USB2.0
Alarm In/Out	8 plus36 switch value /4 plus 18 switch value(extended board)
Advance	
NAS	NFS Protocol, Support Manual Backup Only
Plug and Play	Y, Only for Tiandy Cameras
Image Flip	Y, Only for Tiandy Cameras
Hot Standby	N+M
Corridor Mode	Y, 16:9 to 9:16, Only for Tiandy Cameras
Video Analytics(VCA)	Tripwire/Double Tripwire/Perimeter/Object Abandon/Object Lost/Running/Loitering/Parking/Early Warning/Crowd/Face Detection/People Counting/Audio Abnormal Detection/Video Abnormal Detection/On duty Detection/Intelligent tracking/Heat map
Smart Search	Quickly Search Target Videos according to Channel No., Records Type, Records Time, File Type and VCA( Only for Tiandy Cameras )
Trigger Recording	Manual/Timing/Motion Detection/Port Alarm/VCA/Video Occlusion
Smart Recording	Set Different Recording Bite Rate for Different Time
Alarm Recording	Pre Alarm Default 10s ( 5/10/15/60s Optional ), Post Alarm Default 10s (10/15/30/60/600s Optional ).
One Key Control	Intercom, Recording
Records Format	SDV, Export MP4 in H.264 Format
Records Encryption	Y
Records Tag	Y
Onvif	Onvif(Profile S)
General	
Language	English, Spanish, Korean, Italian, Turkish, Thai, Russian, Polish, French, Traditional Chinese, Simplified Chinese, Dutch, Hebrew ( UI)
Power Supply	100 ~ 240V AC, 50 ~ 60Hz, 1+1 redundant power
Consumption(without HDD)	Max 610w, Average 650w
Working Temperature	0°C ~ 50°C
Working Humidity	10 % ~ 90 %
Chassis	4U
Dimensions	542mm×446.6mm×173.8mm
Weight	25Kg (without HDD)