

Indoor Dome IP Camera

FEATURES

- Triple Streaming.
- H.264 & MPEG4 & M-JPEG Video Compression.
- Digital Noise Reduction
- Privary Mask
- Support AWB, AES, AGC and Flickess Application
- Support Multi-Event Application
- Support Mahority Network Protocol
- Support Two Way Audio
- Support Mirco SD Card application (Class 6)
- Miulti-Browser View
- Mobile Application (Android / iOS (iPhone, iPad))
- ONVIF Standard



SPECIFICATIONS

Series	8 Series	D Series
	RYK-IP4831/1 H.264 Full HD	RYK-IP4D31/1 H.264 Full HD, WDR
Image Sensor	1/2.7" Progressive CMOS Sensor.	1/3" SONY "Exmor" Progressive CMOS Sensor.
Resolution	2.0 MegaPixel Resolution	3.0 MegaPixel Resolution
Frame Rate	1080P Up to 30FPS	
Lens	Vari-Focal Lens(with ICR) 2.8~10mm/F1.2	
ICR	Built in IR-CUT Removable (ICR) Module	
Video	Composite Video BNC Out	
Audio	Built in Mic IN / LINE IN / LINE OUT	
DI/DO	1 x DI, 1 x DO	
RS485	Yes	
Other Application	-	WDR Application
Power	DC 12V / AC 24V / PoE	
Operating Condition	0°C~ 50°C	

Outdoor Dome IP Camera

FEATURES

- Triple Streaming.
- H.264 & MPEG4 & M-JPEG Video Compression.
- Digital Noise Reduction
- Privary Mask
- Support AWB, AES, AGC and Flickess Application
- Support Multi-Event Application
- Support Mahority Network Protocol
- Support Two Way Audio
- Support Mirco SD Card application (Class 6)
- Miulti-Browser View
- Mobile Application (Android / iOS (iPhone, iPad))
- ONVIF Standard



SPECIFICATIONS

Series	8 Series	D Series
	RYK-IP6831 H.264 Full HD	RYK-IP6D31 H.264 Full HD, WDR
Image Sensor	1/2.7" Progressive CMOS Sensor.	1/2.8" SONY "Exmor" Progressive CMOS Sensor.
Resolution	2.0 MegaPixel Resolution	3.0 MegaPixel Resolution
Frame Rate	1080P Up to 30FPS	
Lens	Megapixel Vari-focal Lens, f=2.8~10mm, F=1.2	
ICR	Built in IR-CUT Removable (ICR) Module	
Video	Composite Video BNC Out	
Audio	LINE IN / LINE OUT	
DI/DO	1 x DI, 1 x DO	
RS485	Yes	
Other Application	-	WDR Application
Power	DC 12V / PoE	
Operating Condition	-30°C~ 50°C (Built in Heater)	