

AXIS Companion Eye mini L

Indoor full HD IR network camera

AXIS Companion Eye mini L is a small and discreet, indoor day/night camera with built-in IR illumination for surveillance in total darkness. The mini dome has a compact, flat-faced design that suppresses reflections, and WDR technology delivering high image quality even in scenes with complex light conditions. The camera features Power over Ethernet (PoE) that allows one cable to provide both network connectivity and electrical power. AXIS Companion Eye mini L is supported only by AXIS Companion video management software and mobile app, and requires an AXIS Companion Recorder for system completion.

- > **High video quality in HDTV 1080p and 2 MP resolution**
- > **Built-in IR illumination for surveillance in total darkness**
- > **WDR to handle scenes with complex light conditions**
- > **PoE for network connectivity and electrical power**
- > **Optimized for reduced bandwidth and storage need**



AXIS Companion Recorder is required and sold separately

AXIS Companion Eye mini L

Camera		Typical 2.1 W, max 3.2 W
Image sensor	1/2.8" progressive scan RGB CMOS	Connectors
Lens	Horizontal field of view: 103° Vertical field of view: 55° Fixed iris and IR corrected	T/100BASE-TX PoE
Day and night	Automatically removable infrared-cut filter	IR illumination
Minimum illumination	0 lux with IR illumination on	Power-efficient, long-life 850 nm IR LED. Range of reach up to 15 m (49 ft) depending on scene
Camera angle adjustment	Pan: +/-177° Tilt: 30° to 90° Rotation: 0°, 90°, 180°, 270° Can be directed in any direction	Storage
Video		AXIS Companion Recorder is required
Video compression	H.265 (MPEG-H Part 2)	Operating conditions
Resolution	1920x1080 HDTV 1080p and 640x360	0 °C to 50 °C (32 °F to 122 °F) Humidity 10–85% RH (non-condensing)
Frame rate	Up to 25/30 fps with power line frequency 50/60 Hz	Storage conditions
Video streaming	Multiple, individually configurable streams Controllable frame rate	-40 °C to 65 °C (-40 °F to 149 °F)
Image settings	Color, brightness, sharpness, contrast, white balance, exposure control, rotation: 0°, 90°, 180°, 270°, including Corridor Format, privacy masks	Approvals
Wide dynamic range	WDR	EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, VCCI Class A, ICES-003 Class A, RCM AS/NZS CISPR 32 Class A Safety IEC/EN/UL 62368-1 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 60529 IP42 Network NIST SP500-267
Network		Dimensions
Security	Password protection, HTTPS ^a encryption, digest authentication, user access log, brute force delay protection, signed firmware	Height: 58 mm (2 9/32 in) ø 86 mm (3 25/64 in)
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , Bonjour, UPnP®, DNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP	Weight
System integration		120 g (0.26 lb)
Event triggers	Video motion detection	Included accessories
General		Installation guide
Casing	IP42, Plastic PC/ABS Color: white NCS S 1002-B For repainting instructions of casing and impact on warranty, contact your Axis partner.	Optional accessories
Sustainability	PVC free	AXIS T8415 Wireless Installation Tool AXIS T94E01M J-Box/Gang Box Plate AXIS T94E01D Pendant Kit AXIS T91A27 Pole Mount For more accessories, see axis.com
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 1	Video management software
		AXIS Companion available on axiscompanion.com/vms
		Warranty
		Axis 3-year warranty, see axis.com/warranty

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).

Environmental responsibility:

axis.com/environmental-responsibility