

## Dynacom WQ2CMP Series



2M pixel full real time optional  
 1920x1080 / 30fps  
 3.6mm (Optional 2.8/6mm) 3MP Lens  
 Built-in IR-CUT.Low power consumption  
 Micro SD 128GB support  
 H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG  
 Support Multiple-Stream  
 Support ONVIF protocol

| CAMERA                     |  |
|----------------------------|--|
| <b>Model</b>               | <b>WQ2CMP</b>  |
| Case                       | Metal, Dome  |
| Image Sensor               | 1/2.9" SONY Low Illumination CMOS Sensor                           |
| Max Resolution / FPS       | 1920x1080 / 30fps  |
| Min. illumination          | 0.1Lux @ F1.2 (Color) (0 Lux IR LED On)                            |
| Day / Night                | Day / Night with ICR Filter.                                       |
| IR Leds                    | 18pcs* $\phi$ , IR Range: 30M                                      |
| Lens                       | 3.6mm Fixed Lens (2.8/6mm Optional)                                |
| Lens Pixels                | 3MP  |
| Video Output               | Main stream:1920*1080@30fps  |
|                            | Sub stream:704*576@30fps   |
|                            | Tri stream:352*288@30fps   |
| PARAMETERS                 |  |
| Compression                | H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG                           |
| Bit Rate (CBR/VBR)         | 32Kbps-16Mbps continuously adjustable, support CBR/VBR             |
| Shutter Time               | Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec                    |
| S/N Ratio                  | $\geq$ 52dB  |
| NETWORK                    |  |
| Network Port               | One RJ45 Ethernet interface, 10M/100M self-adaption                |
| Standard protocol          | Onvif 2.4  |
| Network Protocols          | TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP    |
| Mobile phone monitor       | Support mobile phone monitor ( iPhone, iPad, Android, Android Pad) |
| IE Brower                  | IE8-11, Google Chrome, Firefox, Safari, Mac Safari                 |
| CONNECTOR                  |  |
| Audio Input (Optional)     | 1CH audio MIC input/Line in  |
| Audio Output (Optional)    | 1CH audio output   |
| IO function port           | Reset (Optional)   |
| Alarm in/output (Optional) | 1* Alarm input port/1*Alarm output port                            |
| SD Card                    | Micro SD 128GB   |
| GENERAL                    |  |
| power                      | DC12V / PoE (802.3af) power input port, 5w power                   |
| Working Temperature        | -20°C ~ +60°C RH95% Max  |
| Housing                    | Metal, IP66  |
| Product Dimensions         | $\phi$ 94.5 x 76(H) mm   |
| Weight                     | 450g   |