

NEI-NVR9600 SERIES NVR



Features and Functions

Professional and Reliable

- New logical and visualized GUI design
- Dual-OS design to ensure high reliability of system running
- ANR technology to enhance the storage reliability when the network is disconnected
- HDD hot swap with RAID0, RAID1, RAID5, RAID6 and RAID10 storage scheme configurable
- Configurable normal or hot spare working mode to constitute an N+1 hot spare system

Video Input and Transmission

- Adopt stream over TLS encryption technology (enhanced SDK service and RTP over HTTPS protocol) which provides more secure stream transmission service (max. 128 Mbps TLS stream outgoing bandwidth, when RAID is enabled, it will restrict TLS stream outgoing bandwidth to 64 Mbps)
- Up to 64-ch IP cameras can be connected (up to 12 MP)
- Connectable to the third-party network cameras

Compression and Recording

- H.265+ compression effectively reduces the storage space by up to 75%
- Full channel recording at up to 12MP resolution

HD Video Output

- HDMI1/VGA1 and HDMI2/VGA2 outputs provided
- HDMI1 Video output at up to 4K (3840 × 2160) resolution

Storage and Playback

- Up to 8 SATA interfaces and 1 eSATA interface for HDD connection
- 10TB capacity for each HDD
- 8/16-ch synchronous playback at up to 1080p resolution
- Important files management
- HDD health monitoring

Smart & POS Function

- Supports multiple VCA (Video Content Analytics) events
- Smart search for the selected area in the video; and smart playback to improve the playback efficiency
- Supports VCA search for fire/ship/temperature/temperature difference detection triggered video files
- POS information overlay on live view and playback
- POS triggered recording and alarm

Network & Ethernet Access


- Hik-Connect for easy network management
- 2 Gigabit Ethernet network interfaces



Specifications

| Model | | NEI-NVR9616 | NEI-NVR9632 |
|--------------------|---------------------------------|---|-------------|
| Video/Audio input | IP video input | 16-ch Up to 12 MP resolution | 32-ch |
| | Two-way audio | 1-ch, RCA (2.0 Vp-p, 1 k Ω) | |
| Network | Incoming bandwidth | 256 Mbps or 200 Mbps (when RAID is enabled) | 320 Mbps |
| | Outgoing bandwidth | 256 Mbps, or 200 Mbps (when RAID is enabled) | |
| | Remote connection | 128 | |
| Video/Audio output | Recording resolution | 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF /2CIF/CIF/QCIF | |
| | CVBS output (Optional) | 1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480 | |
| | VGA1 /HDMI1 output resolution | HDMI1: 4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz VGA1: 2K (2560 × 1440)/60Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz | |
| | VGA2 /HDMI2 output resolution | 1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz | |
| | Audio output | 2-ch, RCA (2.0Vp-p, 1 KΩ) | |
| Decoding | Decoding format | H.265/H.265+/H.264/H.264+/MPEG4 | |
| | Live view/Playback resolution | 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF /2CIF/CIF/QCIF | |
| | Synchronous playback | 16-ch | |
| | Capability | 2-ch @ 12 MP (20fps) / 4-ch @ 8 MP (25fps) / 8-ch @ 4MP (30fps) / 16-ch @ 1080p (30fps) | |
| Network management | Network protocols | TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS | |
| Hard disk | SATA | 8 SATA interfaces | |
| | eSATA | 1 eSATA interface | |
| | Capacity | Up to 10TB capacity for each HDD | |
| Disk array | Array type | RAID0, RAID1, RAID5, RAID6, RAID10 | |
| | Number of arrays | 4 | |
| External interface | Network interface | 2, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface | |
| | Serial interface | RS-232; RS-485; Keyboard | |
| | USB interface | Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0 | |
| | Alarm in/out | 16/4 | |
| General | Power supply | 100 to 240 VAC, 50 to 60 Hz | |
| | Max. Power | 200 W | |
| | Consumption (without hard disk) | ≤ 30 W | |
| | Working temperature | -10 °C to 55 °C (14 °F to 131 °F) | |
| | Working humidity | 10 to 90 % | |
| | Dimensions(W × D × H) | 445 × 470 × 90 mm (17.5" × 18.5" × 3.5") | |
| | Weight (without hard disk) | ≤ 10 kg (22 lb) | |

Physical Interfaces



| Index | Description | Index | Description |
|-------|-----------------------|-------|-----------------------------|
| 1 | LAN1/LAN2 Interface | 7 | RS-232 Interface |
| 2 | LINE IN | 8 | eSATA Interface |
| 3 | AUDIO OUT | 9 | Alarm In/Alarm Out |
| 4 | HDMI1/HDMI2 Interface | 10 | 100 to 240 VAC power supply |
| 5 | VGA1/VGA2 Interface | 11 | Power Switch |
| 6 | USB 3.0 Interface | 12 | GND |

Available Models

NEI-NVR9616, NEI-NVR9632

Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
T +27 (10) 0351172
sale.africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

0401701081128