

Dynacom WQ975ZV Series Bullet Camera



5M pixel
 1920x1080 50/60fps
 1/2.8"SONY Starvis Back-illuminated CMOS sensor
 2.7-13.5mm 5MP Lens, 5x zoom
 Motor Zoom Auto Focus Lens
 Built-in IR-CUT.Low power consumption
 IR Distance 50m Max.
 Micro SD 128GB support
 H.264/H.264+/H.265/H.265+/JPEG/MJPEG Compression Method
 IP67 Outdoor Metal Case

CAMERA		
Model	WQ975ZV	WQ975ZAI
Case	Metal, Bullet	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor	
Max Resolution	5M / 2560x1920	
Min. illumination	0.001Lux @ F1.2 (Color) 0.01Lux @ F1.2 (0 Lux IR LED On)	
Day / Night	Day / Night with ICR Filter.	
IR Leds	42μ x 4pcs*, IR Range: 50M	
Lens	2.7 -13.5mm Motorized Lens	
Focus	Auto Focus	
Video Output	Main stream: 2560*1920@25/30fps / 1920x1080@50/60fps	
	Sub stream: 720*480@30fps	
	Tri stream: 352*288@30fps	
Image Setting	Brightness, Contrast, Sharpness, Backlight Compensation	
WDR	120dB	
Privacy Masking	4 Areas	
PARAMETERS		
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG	
Bit Rate (CBR/VBR)	32Kbps-16Mbps continuously adjustable, support CBR/VBR	
Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec	
S/N Ratio	≥52dB	
NETWORK		
Network Port	One RJ45 Ethernet interface, 10M/100M self-adaption	
Standard protocol	ONVIF Profile S	
Network Protocols	TCP/IP,UDP, ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP,SNMP,PPPoE, UPnP,IGMP, 802.1X, QoS, IPv6, Bonjour	
Mobile phone monitor	Support mobile phone monitor (iPhone, iPad, Android, Android Pad)	
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari	
AI FUNCTION		
Intelligent Analysis	Motion Detc., Tampering Alarm	Intrusion Detc., Line Cross Detc., Loiter Detc., People Gather Detc.,
CONNECTOR		
Audio Input (Optional)	1CH audio MIC input/Line in	
Audio Output (Optional)	1CH audio output	
Alarm in/output (Optional)	1* Alarm input port/1*Alarm output port	
SD Card	Micro SD 128GB	
GENERAL		
power	DC12V±10%, 950mA / PoE (802.3af)	
Working Temperature	-30°C ~ +60°C RH95% Max	
Housing	Metal, IP67	
Product Dimensions	179(W) x 90(H) x 90(D)mm	
Weight	900g	
Regulatory	CE / FCC / RoHS	